

Surface Mounting Chip LED

GW Type

Conventional Part No.	Global Part No.	Lighting Color
LN1261C - (TR)	LNJ261C3RRA	Red
LN1361C - (TR)	LNJ361C3GRA	Green
LN1461C - (TR)	LNJ461C3XRA	Amber
LN1861C - (TR)	LNJ861C3DRA	Orange

■ Absolute Maximum Ratings (T_a = 25°C)

Lighting Color	P _D (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{opr} (°C)	T _{stg} (°C)
Red	60	20	60	4	-25 ~ +80	-30 ~ +85
Green	60	20	60	4	-25 ~ +80	-30 ~ +85
Amber	60	20	60	4	-25 ~ +80	-30 ~ +85
Orange	60	20	60	3	-25 ~ +80	-30 ~ +85

I_{FR}の条件は duty 10% Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec

■ Electro-Optical Characteristics (T_a = 25°C)

Conventional Part No.	Lighting Color	Lens Color	I _O			V _F		λ _p	Δλ	I _F	I _R	
			Typ	Min	I _F	Typ	Max				Max	V _R
LN1261C - (TR)	Red	Clear	1.4	0.5	15	2.2	2.8	700	100	20	5	4
LN1361C - (TR)	Green	Clear	7.5	2.8	20	2.2	2.8	565	30	20	10	4
LN1461C - (TR)	Amber	Clear	4.5	1.6	20	2.2	2.8	590	30	20	10	4
LN1861C - (TR)	Orange	Clear	5.0	1.9	20	2.1	2.8	630	40	20	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

