

NC7SZ66

TinyLogic® Low Voltage UHS Single SPST Normally Open Bus Switch

General Description

The NC7SZ66 is a ultra high-speed (UHS) CMOS compatible single-pole/single-throw (SPST) bus switch. The LOW On Resistance of the switch allows inputs to be connected to outputs with minimal propagation delay and without generating additional ground bounce noise. The device is organized as a 1-bit switch with a switch enable (OE) signal. When OE is HIGH, the switch is on and Port A is connected to Port B. When OE is LOW, the switch is open and a high-impedance state exists between the two ports.


Features

- Space saving SOT23 or SC70 5-lead package
- Ultra small MicroPak™ leadless package
- Broad V_{CC} Operating Range 1.65V–5.5V
- Rail-to-rail signal handling
- 5Ω switch connection between two ports
- Minimal propagation delay through the switch
- Low I_{CC}
- Zero bounce in flow-through mode
- Control input compatible with CMOS input levels

Ordering Code:


| Order Number | Package Number | Product Code Top Mark | Package Description | Supplied As |
|--------------|----------------|-----------------------|---------------------------------------|---------------------------|
| NC7SZ66M5X | MA05B | 7Z66 | 5-Lead SOT23, JEDEC MO-178, 1.6mm | 3k Units on Tape and Reel |
| NC7SZ66P5X | MAA05A | Z66 | 5-Lead SC70, EIAJ SC-88a, 1.25mm Wide | 3k Units on Tape and Reel |
| NC7SZ66L6X | MAC06 | EE | 6-Lead MicroPak, 1.0mm Wide | 5k Units on Tape and Reel |

Logic Symbol




Connection Diagrams

Pin Assignments for SC70



(Top View)

Pad Assignment for MicroPak



(Top Through View)

Pin Descriptions

| Pin Names | Description |
|-----------|---------------------|
| OE | Switch Enable Input |
| A | Bus A I/O |
| B | Bus B I/O |
| NC | No Connect |

Function Table

| OE | B ₀ | Function |
|----|----------------|------------|
| L | HIGH-Z State | Disconnect |
| H | A ₀ | Connect |

TinyLogic® is a registered trademark of Fairchild Semiconductor Corporation.
MicroPak™ is a trademark of Fairchild Semiconductor Corporation.

Absolute Maximum Ratings (Note 1)

| | |
|----------------------------------------------------------------|--------------------------|
| Supply Voltage (V_{CC}) | -0.5V to +7.0V |
| DC Switch Voltage (V_S) | -0.5V to $V_{CC} + 0.5V$ |
| DC Input Voltage (V_{IN}) (Note 2) | -0.5V to +7.0V |
| DC Input Diode Current (I_{IK}) $V_{IN} < 0V$ | -50 mA |
| DC Output (I_{OUT}) Sink Current | 128 mA |
| DC V_{CC}/GND Current (I_{CC}/I_{GND}) | ± 100 mA |
| Storage Temperature Range (T_{STG}) | -65°C to +150°C |
| Junction Lead Temperature under Bias (T_J) | +150°C |
| Junction Lead Temperature (T_L) (Soldering, 10 Seconds) | +260°C |
| Power Dissipation (P_D) @ +85°C | |
| SOT23-5 | 200 mW |
| SC70-5 | 150 mW |

Recommended Operating Conditions (Note 3)

| | |
|-----------------------------------------|-----------------|
| Power Supply Operating (V_{CC}) | 1.65V to 5.5V |
| Control Input Voltage (V_{IN}) | 0V to 5.5V |
| Switch Input Voltage (V_{IN}) | 0V to V_{CC} |
| Switch Output Voltage (V_{OUT}) | 0V to V_{CC} |
| Input Rise and Fall Time (t_r, t_f) | |
| Control Input; $V_{CC} = 2.3V-3.6V$ | 0 ns/V to 10 ns |
| Control Input; $V_{CC} = 4.5-5.5V$ | 0 ns/V to 5 ns |
| Switch I/O | 0 ns/V to DC |
| Operating Temperature (T_A) | -40°C to +85°C |
| Thermal Resistance (θ_{JA}) | |
| SOT23-5 | 300°C/Watt |
| SC70-5 | 425°C/Watt |

Note 1: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 2: The input and output negative voltage ratings may be exceeded if the input and output diode current ratings are observed.

Note 3: Unused inputs must be held HIGH or LOW. They may not float.

DC Electrical Characteristics

| Symbol | Parameter | V_{CC} (V) | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ | | | $T_A = +25^\circ\text{C}$ | | | Units | Conditions | |
|------------|----------------------------------------------------|-----------------|-------------------------------------------------|-----------------|-----|---------------------------|----------|---------------|----------------------------------------------------|---------------------------------------------------|---------------------------------------------------|
| | | | Min | Typ (Note 5) | Max | Min | Typ | Max | | | |
| V_{IH} | HIGH Level | 1.65 to 1.95 | 0.75 V_{CC} | | | | | | V | | |
| | Input Voltage | 2.3 to 5.5 | 0.7 V_{CC} | | | | | | | | |
| V_{IL} | LOW Level | 1.65 to 1.95 | | | | 0.25 V_{CC} | | | V | | |
| | Input Voltage | 2.3 to 5.5 | | | | 0.3 V_{CC} | | | | | |
| I_{IN} | Control Input Leakage Current | 0 to 5.5 | ± 0.05 | ± 1.0 | | | | μA | $0 \leq V_{IN} \leq 5.5V$ | | |
| I_{OFF} | OFF Leakage Current | 1.65 to 5.5 | ± 0.05 | ± 10.0 | | | | μA | $0 \leq A, B \leq V_{CC}$ | | |
| R_{ON} | Switch On Resistance (Note 4) | 4.5 | 3 | | 7 | | Ω | | | $V_{IN} = 0V, I_{IN} = 30 \text{ mA}$ | |
| | | | 5 | | 12 | | | | | | $V_{IN} = 2.4V, I_{IN} = 15 \text{ mA}$ |
| | | | 7 | | 15 | | | | | | $V_{IN} = 4.5V, I_{IN} = 30 \text{ mA}$ |
| | | 3.0 | 4 | | 9 | | | | | | $V_{IN} = 0V, I_{IN} = 24 \text{ mA}$ |
| | | | 10 | | 20 | | | | | | $V_{IN} = 3V, I_{IN} = 24 \text{ mA}$ |
| | | | 5 | | 12 | | | | | | $V_{IN} = 0V, I_{IN} = 8 \text{ mA}$ |
| | | 2.3 | 13 | | 30 | | | | | | $V_{IN} = 2.3V, I_{IN} = 8 \text{ mA}$ |
| | | | 7 | | 28 | | | | | | $V_{IN} = 0V, I_{IN} = 4 \text{ mA}$ |
| | | | 25 | | 60 | | | | | | $V_{IN} = 1.8V, I_{IN} = 4 \text{ mA}$ |
| | | | | | | | | | | | $V_{IN} = 0V, I_{IN} = 4 \text{ mA}$ |
| R_{flat} | On Resistance Flatness (Note 4)(Note 6)(Note 7) | 5.0 | | | | 6 | | | Ω | $I_A = -30 \text{ mA}, 0 \leq V_{Bn} \leq V_{CC}$ | |
| | | 3.3 | | | | 12 | | | | | $I_A = -24 \text{ mA}, 0 \leq V_{Bn} \leq V_{CC}$ |
| | | 2.5 | | | | 28 | | | | | $I_A = -8 \text{ mA}, 0 \leq V_{Bn} \leq V_{CC}$ |
| | | 1.8 | | | | 125 | | | | | $I_A = -4 \text{ mA}, 0 \leq V_{Bn} \leq V_{CC}$ |
| I_{CC} | Quiescent Supply Current | 1.65 to 5.5 | 0.05 | 10 | | | | μA | $V_{IN} = V_{CC} \text{ or } GND$ $I_{OUT} = 0$ | | |

Note 4: Measured by the voltage drop between A and B pins at the indicated current through the switch. On Resistance is determined by the lower of the voltages on the two (A or B) pins.

Note 5: All typical values are at the specified V_{CC} , and $T_A = 25^\circ\text{C}$.

Note 6: Parameter is characterized but not tested in production.

Note 7: Flatness is defined as the difference between the maximum and minimum value of On Resistance over the specified range of conditions.

AC Electrical Characteristics

| Symbol | Parameter | V _{CC} (V) | T _A = -40°C to +85°C, C _L = 50 pF, R _U = R _D = 500Ω | | | Units | Conditions | Figure Number |
|-------------------------------------|------------------------------------------|------------------------|----------------------------------------------------------------------------------------------------|-----------------|------|-------|---------------------------------------------------------------------------------------------------------|------------------|
| | | | Min | Typ (Note 8) | Max | | | |
| t _{PHL} , t _{PLH} | Propagation Delay Bus to Bus (Note 9) | 1.65 to 1.95 | | | 4.3 | | V _{IN} = OPEN | Figures 1, 2 |
| | | 2.3-2.7 | | | 1.2 | ns | | |
| | | 3.0-3.6 | | | 0.8 | ns | | |
| | | 4.5-5.5 | | | 0.3 | ns | | |
| t _{PZL} , t _{PZH} | Output Enable Time | 1.65 to 1.95 | 1.5 | 7.0 | 14.2 | | V _{IN} = 2 x V _{CC} for t _{PZL} V _{IN} = 0V for t _{PZH} | Figures 1, 2 |
| | | 2.3-2.7 | 1.5 | 3.3 | 7.0 | ns | | |
| | | 3.0-3.6 | 1.5 | 2.4 | 5.5 | ns | | |
| | | 4.5-5.5 | 1.5 | 2.0 | 4.5 | ns | | |
| t _{PLZ} , t _{PHZ} | Output Disable Time | 1.65 to 1.95 | 1.5 | 9.2 | 18.2 | | V _{IN} = 2 x V _{CC} for t _{PLZ} V _{IN} = 0V for t _{PHZ} | Figures 1, 2 |
| | | 2.3-2.7 | 1.5 | 5.3 | 9.0 | ns | | |
| | | 3.0-3.6 | 1.5 | 4.0 | 7.0 | ns | | |
| | | 4.5-5.5 | 1.5 | 2.7 | 5.0 | ns | | |


Note 8: All typical values are at the specified V_{CC}, and T_A = 25°C.

Note 9: This parameter is guaranteed by design but is not tested. The switch contributes no propagation delay other than the RC delay of the typical On Resistance of the switch and the 50 pF load capacitance, when driven by an ideal voltage source (zero output impedance).

Capacitance

| Symbol | Parameter | Typ | Max | Units | Conditions |
|------------------|-------------------------------|-----|-----|-------|------------------------|
| C _{IN} | Control Pin Input Capacitance | 2 | | pF | V _{CC} = 0V |
| C _{I/O} | Input/Output Capacitance | 6 | | pF | V _{CC} = 5.0V |

AC Loading and Waveforms



Input driven by 50Ω source terminated in 50Ω
 C_L includes load and stray capacitance.
 Input PRR = 1.0 MHz; $t_w = 500$ ns

FIGURE 1. AC Test Circuit








FIGURE 2. AC Waveforms

Tape and Reel Specification

TAPE FORMAT FOR SOT23, SC70

| Package Designator | Tape Section | Number Cavities | Cavity Status | Cover Tape Status |
|--------------------|--------------------|-----------------|---------------|-------------------|
| M5X, P5X | Leader (Start End) | 125 (typ) | Empty | Sealed |
| | Carrier | 3000 | Filled | Sealed |
| | Trailer (Hub End) | 75 (typ) | Empty | Sealed |

TAPE DIMENSIONS inches (millimeters)



| Package | Tape Size | DIM A | DIM B | DIM F | DIM K ₀ | DIM P1 | DIM W |
|---------|-----------|-----------------|-----------------|-------------------------------|--------------------------------|--------------|----------------------------|
| SC70-5 | 8 mm | 0.093 (2.35) | 0.096 (2.45) | 0.138 ± 0.004 (3.5 ± 0.10) | 0.053 ± 0.004 (1.35 ± 0.10) | 0.157 (4) | 0.315 ± 0.004 (8 ± 0.1) |
| SOT23-5 | 8 mm | 0.130 (3.3) | 0.130 (3.3) | 0.138 ± 0.002 (3.5 ± 0.05) | 0.055 ± 0.004 (1.4 ± 0.11) | 0.157 (4) | 0.315 ± 0.012 (8 ± 0.3) |


NC7SZ66

Tape and Reel Specification (Continued)

TAPE FORMAT FOR MicroPak


| Package Designator | Tape Section | Number Cavities | Cavity Status | Cover Tape Status |
|--------------------|--------------------|-----------------|---------------|-------------------|
| L6X | Leader (Start End) | 125 (typ) | Empty | Sealed |
| | Carrier | 5000 | Filled | Sealed |
| | Trailer (Hub End) | 75 (typ) | Empty | Sealed |

TAPE DIMENSIONS inches (millimeters)




Tape and Reel Specification (Continued)

REEL DIMENSIONS inches (millimeters)





| Tape Size | A | B | C | D | N | W1 | W2 | W3 |
|-----------|----------------|-----------------|------------------|------------------|------------------|---------------------------------------------|------------------|----------------------------------------|
| 8 mm | 7.0 (177.8) | 0.059 (1.50) | 0.512 (13.00) | 0.795 (20.20) | 2.165 (55.00) | 0.331 + 0.059/-0.000 (8.40 + 1.50/-0.00) | 0.567 (14.40) | W1 + 0.078/-0.039 (W1 + 2.00/-1.00) |

Physical Dimensions inches (millimeters) unless otherwise noted



LAND PATTERN RECOMMENDATION




- NOTES: UNLESS OTHERWISE SPECIFIED
- A) THIS PACKAGE CONFORMS TO JEDEC MO-178, ISSUE B, VARIATION AA, DATED JANUARY 1999.
 - B) ALL DIMENSIONS ARE IN MILLIMETERS.

MA05BRevC

DETAIL A

**5-Lead SOT23, JEDEC MO-178, 1.6mm
Package Number MA05B**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




NOTES:

- A. CONFORMS TO EIAJ REGISTERED OUTLINE DRAWING SC88A.
- B. DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH.
- C. DIMENSIONS ARE IN MILLIMETERS.

MAA05ARevC

**5-Lead SC70, EIAJ SC-88a, 1.25mm Wide
Package Number MAA05A**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



Notes:

1. JEDEC PACKAGE REGISTRATION IS ANTICIPATED
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y14.5M-1994

MAC06ARevB

**6-Lead MicroPak, 1.0mm Wide
Package Number MAC06A**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com