

V23814-K1306-M130

Parallel Optical Link: PAROLI™ Tx AC

V23815-K1306-M130

Parallel Optical Link: PAROLI™ Rx AC

V23814-K1306-M230

Parallel Optical Link: PAROLI™ Tx DC/MUX-ENC

V23815-K1306-M230

Parallel Optical Link: PAROLI™ Rx DC/DEMUX-DEC

Notes

THE DATA SHEETS HAVE BEEN UPDATED NOVEMBER 1998 AND INCLUDE THE FOLLOWING MAJOR CHANGES:

Module	Changes / New Features
V23814-K1306-M130 PAROLI™ Tx AC	<ul style="list-style-type: none">• Technical drawings: correction of the inch dimensions• Cleaning and soldering conditions• LVDS Input voltage range is increased• PIN 67: Laser ENABLE (LE) input is implemented• PIN 68: Laser ENABLE (-LE) input is implemented
V23815-K1306-M130 PAROLI™ Rx AC	<ul style="list-style-type: none">• Technical drawings: correction of the inch dimensions• Cleaning and soldering conditions• LVDS Input voltage range is increased• PIN 67: SD12 Signal Detect is low active
V23814-K1306-M230 PAROLI™ Tx DC/MUX-ENC	<ul style="list-style-type: none">• Technical drawings: correction of the inch dimensions• Cleaning and soldering conditions• LVDS Input voltage range is increased• PIN 7: V_{EE} (ground)• PIN 66: V_{EE} (ground)
V23815-K1306-M230 PAROLI™ Rx DC/DEMUX-DEC	<ul style="list-style-type: none">• Technical drawings: correction of the inch dimensions• Cleaning and soldering conditions• LVDS Input voltage range is increased