

KTC 2235

Unit in mm

- ## FEATURES

- [illegible]

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	120	V
Collector-Emitter Voltage	V_{CEO}	120	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current	I_C	800	mA

CHARACTERISTIC	SYMBOL	RATING	UNIT
Emitter Current	I_E	-800	mA
Collector Dissipation	P_C	900	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55~150	°C

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cutoff Current	I_{CBO}	$V_{CB}=120\text{ V}, I_E=0$	—	—	100	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=5\text{ V}, I_C=0$	—	—	100	nA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=10\text{ mA}, I_B=0$	120	—	—	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=1\text{ mA}, I_C=0$	5	—	—	V
DC Current Gain	h_{FE}	$V_{CE}=5\text{ V}, I_C=100\text{ mA}$	80	—	240	
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=500\text{ mA}, I_B=50\text{ mA}$	—	—	1.0	V
Base-Emitter Voltage	V_{BE}	$V_{CE}=5\text{ V}, I_C=500\text{ mA}$	—	—	1.0	V
Transition Frequency	f_T	$V_{CE}=5\text{ V}, I_C=100\text{ mA}$	—	120	—	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{ V}, I_E=0, f=1\text{ MHz}$	—	—	30	pF

0	80-160	Y	120-240
---	--------	---	---------