

MN39116AT

Diagonal 4.5 mm (type-1/4) 270k-pixel CCD Area Image Sensor

■ Overview

The MN39116AT is a 4.5 mm (type-1/4) interline transfer CCD (IT-CCD) solid state image sensor device.

This device uses photodiodes in the optoelectric conversion section and CCDs for signal readout. The electronic shutter function has made an exposure time of 1/10000 seconds possible. Further, this device has the features of high sensitivity, low noise, broad dynamic range, and low smear.

This device has a total of 267 206 pixels (542 horizontal × 493 vertical) and provides stable and clear images with a resolution of 360 horizontal TV-lines and 350 vertical TV-lines.

Part Number	Size	System	Color or B/W
MN39116AT	4.5 mm (type-1/4)	EIA	B/W


■ Features

- Effective pixel number 512 (horizontal) × 491 (vertical)
- High sensitivity
- Broad dynamic range
- Low smear
- Electronic shutter


■ Applications

- Surveillance cameras
- FA, OA cameras

■ Pin Assignments



■ Block Diagram



■ Pin Descriptions

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	V _{DD}	Power supply	8	Sub	Substrate
2	φ _R	Reset pulse (RG)	9	PT	P-well for protection circuit
3	RD	Reset drain	10	φ _{V1}	Vertical shift register clock pulse 1
4	VO	Video output	11	φ _{V2}	Vertical shift register clock pulse 2
5	LG	Output load transistor gate	12	φ _{V3}	Vertical shift register clock pulse 3
6	φ _{H2}	Horizontal register clock pulse 2	13	φ _{V4}	Vertical shift register clock pulse 4
7	φ _{H1}	Horizontal register clock pulse 1	14	PW	P-well

■ Device Parameter (H × V)

Parameter	Value	Unit
Pixel number *	512 × 491	pixel
Image sensing block dimension	3.6144 × 2.716	mm ²
Pixel dimension	7.2 × 5.6	μm ²

Note) *: OB columns are not included.


■ Absolute Maximum Ratings and Operating Conditions

Parameter		Absolute maximum rating		Operating condition			Unit
		Lower limit	Upper limit	Min	Typ	Max	
V_{DD}		-0.2	18.0	14.5	15.0	15.5	V
V_{RD}		-0.2	18.0	14.5	15.0	15.5	V
$V_{PT}^{*3, 4}$		-10.0	0.2	-8.3	-8.0	-7.7	V
GND		(Referene voltage)		—	0	—	V
V_{LG}^{*6}		(Supplied internally)					V
V_{OG}		(Supplied internally)					V
$V_{\phi R}$	High-Low	—	8.0	3.0	3.3	5.3	V
	Bias	(Supplied internally)					V
$V_{\phi H1}$	High	—	8.0	3.0	3.3	5.3	V
	Low	-0.2	—	-0.05	0	0.05	V
$V_{\phi H2}$	High	—	8.0	3.0	3.3	5.3	V
	Low	-0.2	—	-0.05	0	0.05	V
V_{Sub}^{*2}		(Supplied internally)					V
ϕV_{Sub}^{*1}		-0.2	45.0	22.5	23.0	23.5	V
$V_{\phi V1}^{*3, 4, 5}$	High	—	18.0	14.5	15.0	15.5	V
	Middle	—	—	-0.2	0	0.2	V
	Low	-9.0	—	-8.3	-8.0	-7.7	V
$V_{\phi V2}^{*3, 4, 5}$	Middle	—	15.0	-0.2	0	0.2	V
	Low	-9.0	—	-8.3	-8.0	-7.7	V
$V_{\phi V3}^{*3, 4, 5}$	High	—	18.0	14.5	15.0	15.5	V
	Middle	—	—	-0.2	0	0.2	V
	Low	-9.0	—	-8.3	-8.0	-7.7	V
$V_{\phi V4}^{*3, 4, 5}$	Middle	—	15.0	-0.2	0	0.2	V
	Low	-9.0	—	-8.3	-8.0	-7.7	V
Operating temperature		-10	60	—	25	—	°C
Storage temperature		-30	80	—	—	—	°C

Note) 1. Standard photo detecting condition

Standard photo detecting condition stands for detecting image with a light source of color temperature of 2856K, luminance of 1050 cd/m², and using a color temperature conversion filter LB-40 (HOYA), infrared cut filter CAW-500S with thickness 2.5 mm for a light path and with F8 lens aperture. The quantity of the incidental light to a photo-detecting surface under the above condition is defined as the standard quantity of light.

2. *1: V_{Sub} when using electronic shutter function



■ Absolute Maximum Ratings and Operating Conditions (continued)

Note) 2. *2: V_{Sub} supplied internally is the voltage suppressing the blooming generation at $\times 1\,000$ light quantity relative to the standard light quantity.

*3: Relation between V_{PT} and $V_{\phi VL}$

Set V_{PT} under the following condition against VL of a vertical transfer clock waveform.

$$V_{PT} \leq VL (V_{\phi V1L} \text{ to } V_{\phi V4L})$$

*4: Absolute maximum ratings $-0.2 < V_{Sub} - V_{PT} < 55 (V)$
 $-0.2 < V_{\phi V} - V_{PT} < 24.5 (V)$

*5: Ground LG pin with the capacitor of $0.047 \mu F$ or more.


Ground ϕ_R pin with the capacitor of $1 M\Omega$.

■ Optical Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
S/N ratio (dark)	S/Nd	Dark condition	58	60	—	dB
Sensitivity	So	J chart F8	480	650	—	mV
Saturation output	Sc	Saturation maximum output	700	900	—	mV
Vertical smear	Sm	1/10 V chart, F2.8	—	—	0.01	%


■ Graph of Characteristics

CCD spectral characteristics



■ Timing Diagram


- High speed pulse timing




■ Timing Diagram (continued)

- Rise time and fall time of each pulse


ϕ_{V1}, ϕ_{V3}




ϕ_{V2}, ϕ_{V4}



$\phi_{H1}, \phi_{H2}, \phi_R$




DS1, DS2



■ Package Dimensions (unit: mm)

- WDIP014-P-0400F



Request for your special attention and precautions in using the technical information and semiconductors described in this material

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this material is limited to showing representative characteristics and applied circuits examples of the products. It neither warrants non-infringement of intellectual property right or any other rights owned by our company or a third party, nor grants any license.
- (3) We are not liable for the infringement of rights owned by a third party arising out of the use of the product or technologies as described in this material.
- (4) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (5) The products and product specifications described in this material are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (6) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage, and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (7) When using products for which damp-proof packing is required, observe the conditions (including shelf life and amount of time let standing of unsealed items) agreed upon when specification sheets are individually exchanged.
- (8) This material may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.