

PNP Silicon Planar Transistors


2 N 2906

SIEMENS AKTIENGESELLSCHAFT **D T-37-17**

2 N 2907

2 N 2906 and 2 N 2907 are epitaxial PNP silicon planar transistors in TO 18 case (18 A 3 DIN 41876). The collector is electrically connected to the case. The transistors are particularly suitable for use as high-speed switches.

Type	Ordering code
2 N 2906	Q62702-F137
2 N 2907	Q62702-S111



Approx. weight 0.3 g

Dimensions in mm

Maximum ratings

Collector-emitter voltage
 Collector-base voltage
 Emitter-base voltage
 Collector current
 Junction temperature
 Storage temperature range
 Total power dissipation ($T_{amb} = 25\text{ °C}$)
 Total power dissipation ($T_{case} = 25\text{ °C}$)

	2 N 2906	2 N 2907
$-V_{CEO}$	40	V
$-V_{CBO}$	60	V
$-V_{EBO}$	5	V
$-I_C$	0.6	A
T_j	200	°C
T_{stg}	-65 to +200	°C
P_{tot}	0.4	W
P_{tot}	1.8	W

Thermal resistance

Junction to ambient air
 Junction to case

R_{thJA}	< 438	K/W
R_{thJC}	< 97	K/W

Static characteristics ($T_{amb} = 25\text{ °C}$)

		2 N 2906	2 N 2907	
Collector-base breakdown voltage ($-I_C = 10\text{ }\mu\text{A}$)	$-V_{(BR)CBO}$	> 60	> 60	V
Collector-emitter breakdown voltage ($-I_C = 10\text{ mA}$)	$-V_{(BR)CEO}$	> 40	> 40	V
Emitter-base breakdown voltage ($-I_E = 5\text{ V}$)	$-V_{(BR)EBO}$	> 5	> 5	V
Collector-emitter saturation voltage ($-I_B = 15\text{ mA}$; $-I_C = 150\text{ mA}$)	$-V_{CEsat}$	< 0.4	< 0.4	V
($-I_B = 50\text{ mA}$; $-I_C = 500\text{ mA}$)	$-V_{CEsat}$	< 1.6	< 1.6	V
Base-emitter saturation voltage ($-I_C = 150\text{ mA}$; $-I_B = 15\text{ mA}$)	$-V_{BEsat}$	< 1.3	< 1.3	V
($-I_C = 500\text{ mA}$; $-I_B = 50\text{ mA}$)	$-V_{BEsat}$	< 2.6	< 2.6	V
Collector cutoff current ($-V_{CB} = 50\text{ V}$)	$-I_{CBO}$	< 20	< 20	nA
($-V_{CB} = 50\text{ V}$; $T_{amb} = 150\text{ °C}$)	$-I_{CBO}$	< 20	< 20	μA
DC current gain ($-V_{CE} = 10\text{ V}$; $-I_C = 100\text{ }\mu\text{A}$)	h_{FE}	> 20	> 35	-
($-V_{CE} = 10\text{ V}$; $-I_C = 1\text{ mA}$)	h_{FE}	> 25	> 50	-
($-V_{CE} = 10\text{ V}$; $-I_C = 10\text{ mA}$)	h_{FE}	> 35	> 75	-
($-V_{CE} = 10\text{ V}$; $-I_C = 150\text{ mA}$)	h_{FE}	40 to 120	100 to 300	-
($-V_{CE} = 10\text{ V}$; $-I_C = 500\text{ mA}$)	h_{FE}	> 20	> 30	-

Dynamic characteristics ($T_{amb} = 25\text{ °C}$)

Collector base capacitance ($-V_{CB} = 10\text{ V}$; $f = 100\text{ kHz}$)	C_{CBO}	< 8	< 8	pF
Transition frequency ($-V_{CE} = 20\text{ V}$; $-I_C = 50\text{ mA}$; $f = 100\text{ MHz}$)	f_T	> 200	> 200	MHz

Switching times:

($-V_{CC} = 30\text{ V}$; $-I_C = 150\text{ mA}$; I_{B1} approx. I_{B2} approx. 15 mA)				
Delay time	t_d	< 10	< 10	ns
Rise time	t_r	< 40	< 40	ns
Storage time	t_s	< 80	< 80	ns
Fall time	t_f	< 30	< 30	ns