

SEVEN SEGMENT NUMERIC DISPLAY

High Performance GaP/GaP Green LED Chip
0.56 inch Character Height
High Contrast
Wide Viewing Angle
Common Anode - MG456A-GD
Common Cathode - MG456C-GD

ABSOLUTE MAXIMUM RATINGS

Power Dissipation / Segment	Pd	75mW
Peak Forward Current / Segment	IF/Pulse*	100mA
Continuous Forward Current / Segment	IF/DC	25mA
Reverse Voltage / Segment	VR	5V
Operating Temperature Range	Tstg	-25 to +85°C
Storage Temperature Range	Topr	-25 to +85°C

* Note : Pulse Width = 1mS, Duty Ratio = 1/10.

ELECTRO-OPTICAL CHARACTERISTICS(Ta=25°C)

PARAMETER	SYMBOL	MIN	TPY	MAX	UNIT	CONDITIONS
Forward Voltage	VF		2.2	3.0	V	IF=20mA
Luminous Intensity	IV	500	1000		μcd	IF=10mA
Segment to Segment				2:1		IF=10mA
Luminous Intensity Ratio						
Peak Wavelength	λp		570		nm	IF=20mA
Spectral Line Half Width	Δλ		30		nm	IF=20mA




MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Bulding, Kwun Tong, Kowloon, Hong Kong.


Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

Jan-98

MECHANICAL OUTLINE:



CIRCUIT DIAGRAM:



Unit : mm (inch)