

# Surface Mounting Chip LED

## S – J Type

Conventional Part No.      Global Part No.      Lighting Color  
 LNJ206R5RRX ..... LNJ206R5RRX ..... Red  
 LNJ206R5ARA ..... LNJ206R5ARA ..... Ultra Bright Red  
 LNJ306G5URA ..... LNJ306G5URA ..... Green  
 LNJ806K5SRX ..... LNJ806K5SRX ..... Soft Orange

### ■ Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Lighting Color	$P_D$ (mW)	$I_F$ (mA)	$I_{FP}$ (mA)*	$V_R$ (V)	$T_{opr}$ ( $^\circ\text{C}$ )	$T_{stg}$ ( $^\circ\text{C}$ )
Red	60	20	60	4	-25 ~ +85	-30 ~ +100
Ultra Bright Red	60	20	60	3	-25 ~ +85	-30 ~ +100
Green	60	20	60	4	-25 ~ +85	-30 ~ +100
Soft Orange	60	20	60	3	-25 ~ +85	-30 ~ +100

$I_{FR}$ の条件は  $\rho$  duty 10% Pulse width 1 msec. The condition of  $I_{FP}$  is duty 10%, Pulse width 1 msec

### ■ Electro-Optical Characteristics ( $T_a = 25^\circ\text{C}$ )

Conventional Part No.	Lighting Color	Lens Color	$I_O$		$I_F$	$V_F$		$\lambda_P$	$\Delta\lambda$	$I_F$	$I_R$	
			Typ	Min		Typ	Max				Max	$V_R$
LNJ206R5RRX	Red	Red Diffused	0.4	0.15	10	2.03	2.6	700	100	10	5	4
LNJ206R5ARA	Ultra Bright Red	Red Diffused	5.0	1.7	10	1.72	2.5	660	20	10	10	3
LNJ306G5URA	Green	Green Diffused	2.6	0.9	10	2.03	2.6	565	30	10	10	4
LNJ806K5SRX	Soft Orange	Yellow Diffused	0.8	0.3	10	1.93	2.6	610	40	10	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	$\mu\text{A}$	V

