


T-41-21

SIEMENS

**RED LR 3360
SUPER-RED LS 3360
YELLOW LY 3360
GREEN LG 3360**

T1 (3 mm) LED LAMP




FEATURES

- High Light Output
 - Diffused Lens
 - Wide Viewing Angle 70°
 - With Standoffs
 - T1 (3 mm) Package Size
 - 1" Lead Length
 - I/C Compatible

DESCRIPTION

The LR 3360 series is a standard red gallium arsenide phosphide (GaAsP) LED lamp. The LS 3360 super-red and LY 3360 yellow are premium high efficiency light emitting diode lamps fabricated with TSN (transparent substrate nitrogen) technology. The LG 3360 green is a gallium phosphide (GaP) lamp. All have a diffused plastic lens which emits a full flooded intense light.

Package Dimensions mm



Approx weight 0.15 g

Maximum Ratings

Characteristics ($T_s = 25^\circ\text{C}$)

Parameter	Symbol	LR 3360 Red	LS 3360 Super-Red	LY 3360 Yellow	LG 3360 Green	Unit
Wavelength at Peak Emission	λ_{PEAK}	660	635	586	565	nm
Dominant Wavelength	λ_{DOM}	645	628	590	567	nm
Viewing Angle (Limits for 50% of Luminous Intensity I_v)	ϕ	70	70	70	70	deg
Forward Voltage ($I_f = 10 \text{ mA}$)	V_f	1.6 (≤ 2.0)	2.0 (≤ 2.6)	2.0 (≤ 2.6)	2.0 (≤ 2.6)	V
Reverse Current ($V_R = 5 \text{ V}$)	I_R	0.01 (≤ 10)	0.01 (≤ 10)	0.01 (≤ 10)	0.01 (≤ 10)	µA
Capacitance ($V_R = 0 \text{ V}$, $f = 1 \text{ MHz}$)	C_o	25	12	10	15	pF
Rise Time	t_r	120	300	300	450	ns
Fall Time	t_f	90	150	150	200	ns

Luminous Intensity (mcd)

Test				Test			
Part Number	Min.	Max.	Condition	Part Number	Min.	Max.	Condition
LR 3360-DG	0.4	3.2	10 mA	LY 3360-H	2.5	5.0	10 mA
LR 3360-F	1	2	10 mA	LY 3360-HL	2.5	20	10 mA
LR 3360-FJ	1	8	10 mA	LY 3360-J	4	8	10 mA
LR 3360-G	1.6	3.2	10 mA	LY 3360-JM	4	32	10 mA
LS 3360-HL	2.5	20	10 mA	LY 3360-K	6.3	12.5	10 mA
LS 3360-J	4	8	10 mA	LG 3360-GK	1.6	12.5	10 mA
LS 3360-K	6.3	12.5	10 mA	LG 3360-H	2.5	5	10 mA
LS 3360-KN	6.3	50	10 mA	LG 3360-J	4	8	10 mA
LS 3360-L	10	20	10 mA	LG 3360-JM	4	32	10 mA
				LG 3360-K	6.3	12.5	10 mA

See graph numbers 1, 2K (red), 2L (super-red & yellow), 2M (green), 3A, 5A, 6A, 7A, 8, 9, 10 on pages 42 – 48.