


TWL SERIES
Low Leakage Current
◆FEATURES

- RoHS compliance.


◆SPECIFICATIONS

Items	Characteristics																																
Category Temperature Range	-40~+85°C																																
Rated Voltage Range	6.3~50V.DC																																
Capacitance Tolerance	±20% (20°C, 120Hz)																																
Leakage Current(MAX)	$I=0.002CV$ or $0.4\mu A$ whichever is greater. (After 2 minutes application of rated voltage) I =Leakage Current(μA) C =Rated Capacitance(μF) V =Rated Voltage(V)																																
Dissipation Factor(MAX) ($\tan \delta$)	$\langle L=7 \rangle$ <table border="1"> <tr> <td>Rated Voltage (V)</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>(20°C, 120Hz)</td> </tr> <tr> <td>$\tan \delta$</td> <td>0.24</td> <td>0.20</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td></td> </tr> </table> $\langle L \geq 11 \rangle$ <table border="1"> <tr> <td>Rated Voltage (V)</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>(20°C, 120Hz)</td> </tr> <tr> <td>$\tan \delta$</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td></td> </tr> </table> When rated capacitance is over 1000 μF , $\tan \delta$ shall be added 0.02 to the listed value with increase of every 1000 μF .	Rated Voltage (V)	6.3	10	16	25	35	50	(20°C, 120Hz)	$\tan \delta$	0.24	0.20	0.16	0.14	0.12	0.10		Rated Voltage (V)	6.3	10	16	25	35	50	(20°C, 120Hz)	$\tan \delta$	0.22	0.19	0.16	0.14	0.12	0.10	
Rated Voltage (V)	6.3	10	16	25	35	50	(20°C, 120Hz)																										
$\tan \delta$	0.24	0.20	0.16	0.14	0.12	0.10																											
Rated Voltage (V)	6.3	10	16	25	35	50	(20°C, 120Hz)																										
$\tan \delta$	0.22	0.19	0.16	0.14	0.12	0.10																											
Endurance	After life test with rated ripple current at conditions stated in the table below, the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±25% of the initial value.</td> <td>Case Size</td> <td>Life Time (hrs)</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> <td>L=7</td> <td>1000</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> <td>L≥11</td> <td>2000</td> </tr> </table>	Capacitance Change	Within ±25% of the initial value.	Case Size	Life Time (hrs)	Dissipation Factor	Not more than 200% of the specified value.	L=7	1000	Leakage Current	Not more than the specified value.	L≥11	2000																				
Capacitance Change	Within ±25% of the initial value.	Case Size	Life Time (hrs)																														
Dissipation Factor	Not more than 200% of the specified value.	L=7	1000																														
Leakage Current	Not more than the specified value.	L≥11	2000																														
Low Temperature Stability Impedance Ratio(MAX)	<table border="1"> <tr> <td>Rated Voltage (V)</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>(120Hz)</td> </tr> <tr> <td>$Z(-25^\circ C)/Z(20^\circ C)$</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>$Z(-40^\circ C)/Z(20^\circ C)$</td> <td>8</td> <td>6</td> <td>6</td> <td>4</td> <td>4</td> <td>3</td> <td></td> </tr> </table>	Rated Voltage (V)	6.3	10	16	25	35	50	(120Hz)	$Z(-25^\circ C)/Z(20^\circ C)$	4	3	2	2	2	2		$Z(-40^\circ C)/Z(20^\circ C)$	8	6	6	4	4	3									
Rated Voltage (V)	6.3	10	16	25	35	50	(120Hz)																										
$Z(-25^\circ C)/Z(20^\circ C)$	4	3	2	2	2	2																											
$Z(-40^\circ C)/Z(20^\circ C)$	8	6	6	4	4	3																											

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency (Hz)		60(50)	120	500	1k	10k≤
Coefficient	0.1~1 μF	0.50	1.00	1.20	1.30	1.50
	2.2~4.7 μF	0.65	1.00	1.20	1.30	1.50
	10~47 μF	0.80	1.00	1.20	1.30	1.50
	100~1000 μF	0.80	1.00	1.10	1.15	1.20
	2200 μF	0.80	1.00	1.05	1.10	1.15

◆PART NUMBER

□□□	TWL	□□□□□	□	□□□	□□	DXL
Rated Voltage	Series	Rated Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

