STANDARD CRYSTAL

• FOX STANDARD SPECIFICATIONS								
PARAMETER	HC49U*	HC49S/49SD	FPX	FE				
Frequency Tolerance @ 25°C	±30PPM	±30PPM	±50PPM	±50PPM				
Frequency Stability	±50PPM	±50PPM	±100PPM	±50PPM				
Operating Temperature Range	-20°C ~ +70°C	-20°C ~ +70°C	-10°C ~ +70°C	-10°C ~ +60°C				

*Optional third lead, vinyl sleeves (HC49U only), and mylar spacer. All specifications subject to change without notice..

** Measurements are displayed in Millimeters.


• Inventory Support

• Standard Packages

• Lowest Pricing


· Fox Quality

• Technical Support



	2 Max ———	
	1,3	_
		4.5 Ma
2		_1

HC49SD Surface Mount





Please Refer To Specification	Sheets For Details
-------------------------------	--------------------

		<u>Please Refer To Specification Sheets For Details</u>									
FREQ (MHz)	CL	HC49U	ESR W MAX	HC49S	ESR W MAX	HC49SD	ESR W MAX	FPX 1	ESR W MAX	FE	ESR W MAX
1.843200	13pF	FOX018S	800								
2.000000	20pF	FOX020S	500								
2.097152	20pF	FOX020S	500								
2.457600	32pF	FOX024S	300								
3.579545	18pF	FOX036S	120	FOXS/036S	200	FOXSD/036S	200	FPX036S	200		
3.686400	SERIES	FOX0368S	120	FOXS/0368S	200	10/03/03/03		FPX0368S	200		
3.686400	20pF	FOX0368-20	120	FOXS/0368-20	200	FOXSD/0368-20	200	FPX0368-20			
4.000000	SERIES	FOX0368-20	100	FOXS/0308-20	150	FUASD/0308-20	200	FPX040A	150		
4.000000	20pF		100			EOVCD/040	150	FPX040A	150		
4.096000	20pF 20pF	FOX040		FOXS/040	150	FOXSD/040					
4.194304	_	FOX0496-20	100	FOXS/0496-20	150	FOVED/041	150				
4.433619	12pF	FOX041	100	FOXS/041	150	FOXSD/041					
	20pF	FOX0443	70	FOXS/0443	150	FOXSD/0443	150	 EDV/040	1.50		
4.915200	SERIES	FOX049	55	FOXS/049	150		150	FPX049	150		
4.915200	20pF	FOX049-20	55	FOXS/049-20	150	FOXSD/049-20	150	FPX049-20	150		
5.000000	20pF	FOX05A	50			FOXSD/05A	120				
6.000000	SERIES	FOX060	40								
6.000000	20pF	FOX060-20	40			FOXSD/060-20	120				
6.144000	30pF	FOX061	40								
6.144000	20pF	FOX061-20	40								
7.372800	SERIES	FOX073	40	FOXS/073	80			FPX073	80		
7.372800	20pF	FOX073-20	40	FOXS/073-20	80	FOXSD/073-20	80	FPX073-20	80		
8.000000	SERIES	FOX080	35	FOXS/080	80			FPX080	80		
8.000000	20pF	FOX080-20	35	FOXS/080-20	80	FOXSD/080-20	80	FPX080-20	80		
8.192000	SERIES	FOX081	35								
8.192000	20pF	FOX081-20	35	FOXS/081-20	80	FOXSD/081-20	80	FPX081-20	80		
9.216000	SERIES	FOX092	35								
9.830400	SERIES	FOX098	35	FOXS/098	60						
9.830400	20pF	FOX098-20	35	FOXS/098-20	60	FOXSD/098-20	60	FPX098-20	60	FE098-20	60
10.000000	SERIES	FOX100	30	FOXS/100	60			FPX100	60		
10.000000	20pF	FOX100-20	30	FOXS/100-20	60	FOXSD/100-20	60	FPX100-20	60	FE100-20	60
11.000000	SERIES	FOX111	30								
11.000000	20pF	FOX111-20	30	FOXS/111-20	60	FOXSD/111-20	60	FPX111-20	60		
11.059200	20pF	FOX115-20	30	FOXS/115-20	60	FOXSD/115-20	60	FPX115-20	60	FE115-20	60
12.000000	SERIES	FOX120	30	FOXS/120	60			FPX120	60	FE113-20	
12.000000	20pF	FOX120-20	30	FOXS/120-20	60	FOXSD/120-20	60	FPX120-20	60		
12.288000	20pF	FOX128-20	30	FOXS/128-20	60	FOXSD/128-20	60	FPX128-20	60		
14.318180	20pF 20pF	FOX128-20 FOX143-20	25	FOXS/128-20 FOXS/143-20	40	FOXSD/128-20 FOXSD/143-20	40	FPX143-20	40	EE142 20	
14.745600	20pF 20pF	FOX143-20 FOX147-20	25	FOXS/143-20 FOXS/147-20	40	FOXSD/143-20 FOXSD/147-20	40	FPX147-20	40	FE143-20	60
15.000000	20pF 20pF	FUX147-20	23	FUAS/147-20		FUASD/147-20		11 X147-20		FE147-20	60
16.000000		EOV160	2.5	EOVE/160	40			EDV160	40	FE150-20	60
16.000000	SERIES	FOX160	25	FOXS/160		FOVED/160 20	40	FPX160	40	EE160.20	
18.432000	20pF SERIES	FOX160-20	25 20	FOXS/160-20	40	FOXSD/160-20		FPX160-20		FE160-20	60
18.432000		FOX184		EOVE/194 20	4.0	EOVED/194 20	4.0	EDV104 20	40		
	20pF	FOX184-20	20	FOXS/184-20	40	FOXSD/184-20	40	FPX184-20	40		
19.660800	SERIES	FOX196	20		4.0			 EDV104 20	40		
19.660800	20pF	FOX196-20	20	FOXS/196-20	40	FOXSD/196-20	40	FPX196-20			
20.000000	SERIES	FOX200	20	FOXS/200	30			FPX200	30		
20.000000	20pF	FOX200-20	20	FOXS/200-20	30	FOXSD/200-20	30	FPX200-20	30	FE200-20	40
22.118400	20pF	FOX221-20	20	FOXS/221-20	30	FOXSD/221-20	30	FPX221-20	30	FE221-20	40
24.000000	20pF	FOX240F-20	20	FOXS/240F-20	30	FOXSD/240F-20	30	FPX240F-20	30	FE240F-20	40
24.576000	20pF	FOX245F-20	20	FOXS/245F-20	30	FOXSD/245F-20	30	FPX245F-20	30	FE245F-20	40
25.000000	20pF	FOX250F-20	20	FOXS/250F-20	30	FOXSD/250F-20	30	FPX250F-20	30	FE250F-20	40
27.000000	20pF					FOXSD/270F-20	30				
32.000000	20pF	FOX320-20 *	40			FOXSD/320-20 *	100	FPX320-20	* 100		
48.000000	20pF	FOX480-20 *	40			FOXSD/480-20 *	100	FPX480-20			
50.000000	20pF	FOX500-20 *	40			FOXSD/500-20 *	100	FPX500-20 3	* 100		
56.448000	18pF					FOXSD/564-18 *	100				
60.000000	20pF	FOX600-20 *	40			FOXSD/600-20 *	100	FPX600-20	* 100		
64.000000	20pF	FOX640-20 *				FOXSD/640-20 *	100	FPX640-20			
	P-	1011070 20	- 10			1 01102/040 20					

^{* 3}rd Overtone. "F" suffix denotes fundamental Rev. 02/10/03