

TLP3503


TRIAC DRIVER
PROGRAMMABLE CONTROLLERS
AC-OUTPUT MODULE
SOLID STATE RELAY

The TOSHIBA TLP3503 consists of a zero voltage crossing turn-on photo-triac optically coupled to a gallium arsenide infrared emitting diode in a 8 lead plastic DIP package.

- Peak Off-State Voltage : 400V (MIN.)
- Trigger LED Current : 10mA (MAX.)
- On-State Current : 0.5A_{rms} (MAX.)
- Isolation Voltage : 2500V_{rms} (MIN.)
- UL Recognized : UL1577, File No. E67349
- Trigger LED Current


CLASSI- FICATION*	TRIGGER LED CURRENT (mA)		MARKING OF CLASSIFICATION
	V _T =6V, T _a =25°C		
	MIN.	MAX.	
(IFT5)	—	5.0	T5
(IFT7)	—	7.0	T5, T7
Standard	—	10	T5, T7, Blank

*Ex. (IFT5) ; TLP3503 (IFT5)
(Note) Application type name for certification test, please use standard product type name, i.e.
TLP3503 (IFT5) : TLP3503



Weight : 0.52g

PIN CONFIGURATION (TOP VIEW)



961001EBC2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)

CHARACTERISTIC			SYMBOL	RATING	UNIT
LED	Forward Current		I _F	50	mA
	Forward Current Derating (Ta≥ 53°C)		ΔI _F / °C	−0.7	mA / °C
	Peak Forward Current (100μs pulse, 100pps)		I _{FP}	1	A
	Reverse Voltage		V _R	5	V
	Junction Temperature		T _j	125	°C
DETECTOR	Off-State Output Terminal Voltage		V _{DRM}	400	V
	On-State RMS Current	Ta=40°C	I _T (RMS)	0.5	A
		Ta=60°C		0.35	
	On-State Current Derating (Ta≥ 40°C)		ΔI _T / °C	−7.2	mA / °C
	Peak Current from Snubber Circuit (100μs pulse, 120pps)		I _{SP}	2	A
	Peak Nonrepetitive Surge Current (50Hz, Peak)		I _{TSM}	5	A
	Junction Temperature		T _j	110	°C
	Storage Temperature Range		T _{stg}	−40~125	°C
Operating Temperature Range		T _{opr}	−20~80	°C	
Lead Soldering Temperature (10s)		T _{sol}	260	°C	
Isolation Voltage (AC, 1 min., R.H.≤ 60%) (Note)		BV _S	2500	Vrms	

(Note) Device considered a two terminal : LED side pins shorted together and DETECTOR side pins shorted together.

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V_{AC}	—	—	120	V_{ac}
Forward Current	I_F	15	20	25	mA
Peak Current from Snubber Circuit	I_{SP}	—	—	1	A
Operating Temperature	T_{opr}	-20	—	80	$^\circ\text{C}$

INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V_F	$I_F = 10\text{mA}$	1.0	1.15	1.3	V
	Reverse Current	I_R	$V_R = 5\text{V}$	—	—	10	μA
	Capacitance	C_T	$V = 0, f = 1\text{MHz}$	—	30	—	pF
DETECTOR	Peak Off-State Current	I_{DRM}	$V_{\text{DRM}} = 400\text{V}, T_a = 110^\circ\text{C}$	—	—	100	μA
	Peak On-State Voltage	V_{TM}	$I_{\text{TM}} = 0.75\text{A}$	—	—	3.0	V
	Holding Current	I_H	$R_L = 100\Omega$	—	—	25	mA
	Critical Rate of Rise of Off-State Voltage	dv/dt	$V_{\text{in}} = 120\text{V}_{\text{rms}}$ (Fig.1)	200	500	—	$\text{V}/\mu\text{s}$
	Critical Rate of Rise of Commutating Voltage	$dv/dt(c)$	$V_{\text{in}} = 120\text{V}_{\text{rms}}, I_T = 0.5\text{A}_{\text{rms}}$ (Fig.1)	—	5	—	$\text{V}/\mu\text{s}$

COUPLED ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	I_{FT}	$V_T = 6\text{V}$	—	—	10	mA
Inhibit Voltage	V_{IH}	$I_F = \text{Rated } I_{\text{FT}}$	—	—	50	V
Leakage in Inhibited State	I_{IH}	$I_F = \text{Rated } I_{\text{FT}}$ $V_T = \text{Rated } V_{\text{DRM}}$	—	200	—	μA
Capacitance (Input to Output)	C_S	$V_S = 0, f = 1\text{MHz}$	—	0.8	—	pF
Isolation Resistance	R_S	$V_S = 500\text{V}$	5×10^{10}	10^{14}	—	Ω
Isolation Voltage	BV_S	AC, 1 minute	2500	—	—	V_{rms}
		AC, 1 second, in oil	—	5000	—	
		DC, 1 minute, in oil	—	5000	—	V_{dc}

Fig.1 : dv/dt TEST CIRCUIT