

TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic


# TC7SB384FU

## Single Bus Switch

The TC7SB384FU provides single bit of high-speed TTL-compatible switching. The low on resistance of the switch allows connections to be made with minimal propagation delay.

The device is organized as just 1-bit low-impedance switch with output-enable ( $\overline{OE}$ ) input. When  $\overline{OE}$  is low, the switch is on and data can flow from port A to port B, or vice versa. When  $\overline{OE}$  is high, the switch is open and a high-impedance state exists between the two ports.

All inputs are equipped with protection circuits against static discharge.




Weight: 0.006 g (typ.)

## Features

- Operating voltage:  $V_{CC} = 4.5 \sim 5.5$  V
- High speed operation:  $t_{pd} = 0.25$  ns (max)
- Low on resistance:  $R_{ON} = 5 \Omega$  (typ.)
- ESD performance: Machine model  $> \pm 200$  V  
Human body model  $> \pm 2000$  V
- TTL level input (control input)
- Package: USV

## Pin Assignment (top view)




980910EBA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

Truth Table

Input	Function
$\overline{\text{OE}}$	
L	A port = B port
H	Disconnect

System Diagram



Maximum Ratings

Characteristics	Symbol	Rating	Unit
Power supply range	$V_{CC}$	-0.5~7.0	V
DC input voltage	$V_{IN}$	-0.5~7.0	V
DC switch voltage	$V_S$	-0.5~7.0	V
Input diode current	$I_{IK}$	-50	mA
Continuous channel current	$I_S$	128	mA
Power dissipation	$P_D$	200	mW
DC $V_{CC}$ /GND current	$I_{CC}/I_{GND}$	$\pm 100$	mA
Storage temperature	$T_{stg}$	-65~150	$^{\circ}\text{C}$

Recommended Operating Conditions

Characteristics	Symbol	Rating	Unit
Supply voltage	$V_{CC}$	4.5~5.5	V
Input voltage	$V_{IN}$	0~5.5	V
Switch voltage	$V_S$	0~5.5	V
Operating temperature	$T_{opr}$	-40~85	$^{\circ}\text{C}$
Input rise and fall time	$dt/dv$	0~10	ns/V

## Electrical Characteristics

## DC Characteristics (Ta = -40~85°C)

Characteristics		Symbol	Test Condition		Min	Typ. (Note1)	Max	Unit
				V <sub>CC</sub> (V)				
Input voltage	"H" level	V <sub>IH</sub>	—	4.5~5.5	2.0	—	—	V
	"L" level	V <sub>IL</sub>	—	4.5~5.5	—	—	0.8	
Input leakage current		I <sub>IN</sub>	V <sub>IN</sub> = 0~5.5 V	5.5	—	—	±1.0	μA
Off-state leakage current (switch off)		I <sub>SZ</sub>	A, B = 0~5.5 V, $\overline{\text{OE}} = V_{CC}$	5.5	—	—	±1.0	μA
ON resistance (Note2)		R <sub>ON</sub>	V <sub>IS</sub> = 0 V	I <sub>S</sub> = 30 mA	4.5	—	5	Ω
				I <sub>S</sub> = 64 mA	4.5	—	5	
			V <sub>IS</sub> = 2.4 V, I <sub>S</sub> = 15 mA	4.5	—	10	15	
Quiescent supply current		I <sub>CC</sub>	V <sub>IN</sub> = V <sub>CC</sub> or GND, I <sub>OUT</sub> = 0	5.5	—	—	10	μA
		ΔI <sub>CC</sub>	V <sub>IN</sub> = 3.4 V (one input)	5.5	—	—	2.5	mA

Note1: Typical values are at V<sub>CC</sub> = 5 V and Ta = 25°C.

Note2: Measured by the voltage drop between A and B pins at the indicated current through the switch. On resistance is determined by the lower of the voltages on the two (A or B) pins.

## AC Characteristics (Ta = -40~85°C)

Characteristics	Symbol	Test Condition		Min	Max	Unit
			V <sub>CC</sub> (V)			
Propagation delay time (bus to bus)	t <sub>pLH</sub> t <sub>pHL</sub>	Figure 1, Figure 2	(Note3) 4.5	—	0.25	ns
Output enable time	t <sub>pZL</sub> t <sub>pZH</sub>	Figure 1, Figure 3	4.5	—	4.0	ns
Output disable time	t <sub>pLZ</sub> t <sub>pHZ</sub>	Figure 1, Figure 3	4.5	—	4.5	ns

Note3: This parameter is guaranteed by design but is not tested. The bus switch contributes no propagation delay other than the RC delay of the typical on resistance of the switch and the 50 pF load capacitance, when driven by an ideal voltage the source (zero output impedance).

## Capacitive Characteristics (Ta = 25°C)

Characteristics		Symbol	Test Condition		Typ.	Unit
				V <sub>CC</sub> (V)		
Control pin input capacitance		C <sub>IN</sub>	(Note4)	5.0	3	pF
Switch terminal capacitance		C <sub>I/O</sub>	$\overline{\text{OE}} = V_{CC}$ (Note4)	5.0	10	pF

Note4: This item is guaranteed by design.

AC Test Circuit




Figure 1

AC Waveform




Figure 2  $t_{pLH}$ ,  $t_{pHL}$





Figure 3  $t_{pLZ}$ ,  $t_{pHZ}$ ,  $t_{pZL}$ ,  $t_{pZH}$

Package Dimensions

SSOP5-P-0.65A

Unit : mm



Weight: 0.006 g (typ.)