


MT1318A-UR

Features

- Low Current Requirements
- IC Compatible
- High Light Output
- Reliable and Rugged

Maximum Ratings (Ta=25°C)

Characteristic	Symbol	Max.	Test Condition	Unit
Forward Current	I _F	30	-	mA
Pulsed Forward Current	I _{FP}	.10	DC=0.1, PW=0.1ms	A
Reverse Voltage	V _R	4.00	-	V
Power Dissipation	P _D	72.00	-	mW
Operating Temperature	T _{opr}	-25 ~ +85	-	°C
Storage Temperature	T _{stg}	-25 ~ +100	-	°C
Junction Temperature	T _j	-	-	°C
Soldering Temperature	T _{sol}	260	for 5 sec. max	°C



Opto-Electrical Characteristics (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	I _F =20mA	-	1.90	2.40	V
Reverse Current	I _R	V _R =4V	-	-	100	μA
Power Output	P _O	I _F =20mA	-	6.50	-	mW
Luminous Intensity	I _v	I _F =20mA	1200.00	2200.00	-	mcd
Half Intensity Beam Angle	θ	-	-	± 24°	-	deg.
Peak Wavelength	λ _p	I _F =20mA	-	644	-	nm
Dominant Wavelength	λ _d	I _F =20mA	-	630	-	nm
Spectral Line Half Width	Δλ	I _F =20mA	-	18	-	nm

MT1318A-UR Graphs

