

TYPE
NAME

ML725B16F

DESCRIPTION

ML7xx16 series are uncooled DFB (Distributed Feedback) laser diodes for 2.5Gbps transmission emitting light beam at 1310nm. $\lambda/4$ shifted grating structure is employed to obtain excellent SMSR performance under 2.5Gbps modulation. Furthermore, ML7xx16 can operate in the wide temperature range from -20°C to 85°C without any temperature control.

FEATURES

- $\lambda/4$ phase shifted grating structure
- Wide temperature range operation (-20°C to 85°C)
- High side-mode-suppression-ratio (typical 45dB)
- High resonance frequency (typical 11GHz)

APPLICATION

2.5Gbps transmission

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Conditions	Ratings	Unit
Po	Output power	CW	6	mW
IF	Laser forward current	-	200	mA
VRL	Laser reverse voltage	-	2	V
IRD	PD forward current	-	2	mA
VRD	PD reverse voltage	-	20	V
Tc	Operation temperature	-	-20 ~ +85	°C
Tstg	Storage temperature	-	-40 ~ +100	°C

ELECTRICAL/OPTICAL CHARACTERISTICS (Tc=25°C)

Symbol	Parameter	Conditions	Limits			Unit
			Min.	Typ.	Max.	
Ith	Threshold current	CW	-	10	15	mA
		CW,Tc=85°C	-	35	50	mA
Iop	Operation current	CW,Po=5mW	-	30	40	mA
		CW,Po=5mW,Tc=85°C	-	75	100	mA
Vop	Operating voltage	CW,Po=5mW	-	1.1	1.8	V
η	Slope efficiency	CW,Po=5mW	0.18	0.25	-	mW/mA
λ_p	Peak wavelength	CW,Po=5mW,Tc=-20°C~+85°C	1290	1310	1330	nm
SMSR	Side mode suppression ratio	CW,Po=5mW,Tc=-20°C~+85°C	35	45	-	dB
θ_{\parallel}	Beam divergence angle (parallel)	CW,Po=5mW	-	25	40	deg.
θ_{\perp}	(perpendicular)	CW,Po=5mW	-	30	47	deg.
fr	Resonance frequency	2.48832Gbps, Ibias=Ith,Ipp=40mA	-	11	-	GHz
tr,tf	Rise and fall time(10%-90%)	2.48832Gbps, Ibias=Ith,Ipp=40mA not including package	-	100	150	psec
Im	Monitoring current (PD)	CW,Po=5mW,VRD=1V	0.1	-	2.0	mA
Id	Dark current (PD)	VRD=5V	-	-	1.0	A
Ct	Capacitance (PD)	VRD=5V,f=1MHz	-	10	20	pF

MITSUBISHI
ELECTRIC

ML7xx16 SERIES

2.5Gbps InGaAsP DFB LASER DIODE

OUTLINE DRAWINGS

