

DIODE Type : 30D2

OUTLINE DRAWING

FEATURES

- * Low Forward Voltage drop
- * Low Reverse Leakage Current
- * High Surge Capability



Maximum Ratings

Approx Net Weight: 1.24g

Rating	Symbol	30D2			Unit
Repetitive Peak Reverse Voltage	V_{RRM}	200			V
Non-repetitive Peak Reverse Voltage	V_{RSM}	400			V
Average Rectified Output Current	I_o	1.7	$T_a=40^\circ C$	*1	A
		3.0	$T_a=61^\circ C$	*2	
RMS Forward Current	$I_{F(RMS)}$	50Hz Half Sine Wave Resistive Load			A
Surge Forward Current	I_{FSM}	150	50Hz Half Sine Wave, 1cycle, Non-repetitive		
Operating Junction Temperature Range	T_{jw}	- 40 to + 150			°C
Storage Temperature Range	T_{stg}	- 40 to + 150			°C

Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions		Min.	Typ.	Max.	Unit
Peak Reverse Current	I_{RM}	$T_j = 25^\circ C$, $V_{RM} = V_{RRM}$		-	-	50	μA
Peak Forward Voltage	V_{FM}	$T_j = 25^\circ C$, $I_{FM} = 3.0A$		-	-	0.93	V
Thermal Resistance	$R_{th(j-a)}$	Junction to Ambient		*1	-	80	°C/W
				*2		34	

*1 : Without Fin or P.C. Board

*2 : With Cu Fin (20 x 20 x 1 t, L = 5mm, Both Sides)

30D2 OUTLINE DRAWING (Dimensions in mm)

