



Description








Mechanical Dimensions



Features

- **HIGH TEMPERATURE METALLURGICALLY BONDED CONSTRUCTION**
- **SINTERED GLASS CAVITY-FREE JUNCTION**
- **1.0 AMP OPERATION @ $T_A = 55^\circ\text{C}$, WITH NO THERMAL RUNAWAY**
- **TYPICAL $I_R < 0.1 \mu\text{Amp}$**

Electrical Characteristics @ 25°C.	GP10A . . . 10M Series							Units
Maximum Ratings	GP10A	GP10B	GP10D	GP10G	GP10J	GP10K	GP10M	
Peak Repetitive Reverse Voltage... V_{RRM}	50	100	200	400	600	800	1000	Volts
RMS Reverse Voltage... $V_{R(rms)}$	35	70	140	280	420	560	700	Volts
DC Blocking Voltage... V_{DC}	50	100	200	400	600	800	1000	Volts
Average Forward Rectified Current... $I_{F(av)}$ Current 3/8" Lead Length @ $T_A = 75^\circ\text{C}$					1.0			Amps
Non-Repetitive Peak Forward Surge Current... I_{FSM} ½ Sine Wave Superimposed on Rated Load					30			Amps
Forward Voltage @ 1.0A... V_F	<	1.1>	<	1.2>		Volts
Full Load Reverse Current... $I_R(av)$ Full Cycle Average @ $T_A = 75^\circ\text{C}$				30				μAmps
DC Reverse Current... I_R @ Rated DC Blocking Voltage	$T_A = 75^\circ\text{C}$			5.0				μAmps
	$T_A = 125^\circ\text{C}$			50				μAmps
Typical Junction Capacitance... C_J (Note 1)	<	8.0>	<	7.0>		pF
Typical Thermal Resistance... $R_{\theta JA}$ (Note 2)				55				°C/W
Typical Reverse Recovery Time... t_{RR} (Note 3)				2.0				μS
Operating & Storage Temperature Range... T_J , T_{STRG}				-65 to 175				°C



Ratings at
25 Deg. C ambient
temperature
unless otherwise
specified.

Single Phase Half
Wave, 60 Hz
Resistive or
Inductive Load.

For Capacitive
Load, Derate
Current by 20%.

- NOTES:**
1. Measured @ 1 MHZ and applied reverse voltage of 4.0V.
 2. Thermal Resistance from Junction to Ambient at 3/8" Lead Length, P.C. Board Mounted.
 3. Reverse Recovery Condition $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $I_{RR} = 0.25\text{A}$.