



NTE7083

Integrated Circuit

Vertical Deflection Circuit for

Monitor Applications

Description:

The NTE7083 is an integrated circuit in a 13-Lead Staggered SIP type package designed for vertical deflection primarily in monitors and TV receivers.

Features:

- Fully Integrated, Few External Components
- RC Oscillator with Wide Sync Range
- Guard Circuit for Screen Protection
- Synchronization by Positive or Negative Going Sync Pulse
- Preamplifier
- Flyback Generator
- Internal Voltage Stabilizer
- Dual Frequency Criterion for Automatic Amplitude Switch-Over

Absolute Maximum Ratings:

Parameter	Symbol	Test Conditions		Min	Max	Unit
Voltages	V ₂			0	6	V
	V ₁₁			0	24	V
	V ₁₂			0	6	V
	V ₁₃			0	50	V
Supply Voltages (V _P)	V ₁₀			0	50	V
	V ₉			0	50	V
	V ₇			0	60	V
	V ₆			0	60	V
	V ₅			0	6	V
	V ₄			0	24	V
	V ₃			-0.7	6	V
Currents	I ₁			0	-1	mA
	I ₃			+3	-10	mA
	I ₄			0	-5	mA
	I ₆ , I ₇ , I ₈			Note 1		
	I ₉				-1.5	+1.5 A
	I ₁₁				-0.1	+3.0 mA

Note 1. I₆, I₇, and I₈ are limited by SOAR protection circuit that ensures that a short-circuit between the output Pin7 and supply voltage or GND does not destroy the output stage. A short circuit may be soldered into the printed circuit board or may sometimes (non-periodically) occur in the applied circuit.

Absolute Maximum Ratings (Cont'd):

Parameter	Symbol	Test Conditions	Min	Max	Unit
Storage Temperature Range	T_{stg}		-25	+150	°C
Operating Ambient Temperature Range	T_A	Note 2	-20	+70	°C
Maximum Junction Temperature	T_{Jmax}	Note 3	-	+150	°C
Total Power Dissipation	P_{tot}	Note 2	-	-	W
ESO Stability	V_{ESO}	Note 4	-2000	+2000	V
Thermal Resistance, Junction-to-Ambient	R_{thJA}		-	20	K/W
Thermal Resistance, Junction-to-Mounting Base	R_{thJMB}		-	5	K/W

Note 2. The maximum value to the operating ambient temperature range and the power dissipation depends on the heatsink.

Note 3. Internally limited by thermal protection: switching temperature point at $T_J = +150^\circ\text{C} \pm 8^\circ\text{C}$.

Note 4. Human body model: $1.5\text{k}\Omega$, 100pF , 5 pulses.

Electrical Characteristics: (All voltages are measured to V_{GND} (Pin8), $T_A = +25^\circ\text{C}$, $V_P = +23\text{V}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Voltage Range (Pin10)	V_P		10	-	45	V
Supply Voltage Range (Pin6)	V_P		10	-	30	V
Supply Current	I_{10}	$V_{10} = 25\text{V}$, $V_5 = 3\text{V}$ without load	-	12	-	mA
Supply Current	I_6	$V_6 = 25\text{V}$, $V_5 = 1\text{V}$ without load	-	20	-	mA
Supply Current	I_6	$V_6 = 25\text{V}$, $V_5 = 3\text{V}$ withput load	-	5	-	mA
Minimum Output Voltage	V_7	$I_7 = 1\text{A}$	-	1.40	1.65	V
Maximum Output Voltage	V_7	$I_7 = 1\text{A}$	$V_6 - 2.3$	$V_6 - 2.0$	-	V
Output Voltage During Flyback	V_9	$I_9 = -1\text{A}$	-	$V_{10} - 2.2$	-	V
Output Current	I_7		-	-	± 1.3	A
Output Current	I_8		-	-	± 1.3	A
Preamplifier Input Current	I_5		-	-0.1	-	μA
Stabilized Voltage	V_1		6.1	6.8	7.3	V
Blanking Pulse Output Voltage	V_3		-	5.7	-	V
Blanking Pulse Output Resistance	R_3		-	300	-	Ω
Blanking Pulse Output Current	I_3		0	-	-3	mA
Blanking Pulse Duration	t_{bl}	$R = 100\Omega$, $C = 10\text{pF}$ (Pin12)	640	680	730	μs
Output Voltage Ramp Generator	V_{11}		0.3	-	20	V
Output Current Ramp Generator	I_{11}		-2	-	15×10^3	μA
Output Voltage Frequency Detector	V_{13}	Lower Frequency $I_{13} = 1\text{mA}$	-	-	1.0	V
Leakage Current Frequency Detector	I_{13}	Higher Frequency $V_{13} = 50\text{V}$	-	-	1.0	μA
Output Voltage Buffer Stage	V_4		0	-	20	V
Output Current Buffer Stage	I_4		-	-	-4.0	mA
Synchronizing Input Voltage	V_3	Positive Sync	1.0	-	6.0	V
Synchronizing Input Voltage	V_3	Negative Sync	-0.5	-	-0.7	V

Electrical Characteristics (Cont'd): (All voltages are measured to V_{GND} (Pin8), $T_A = +25^\circ C$, $V_P = +23V$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Tolerance of Free Running Oscillator		Without Sync	-3.0	-	+3.0	%
Oscillator Temperature Dependency	$\Delta f/f / \Delta T_C$	$T_A = +20^\circ$ to $+100^\circ C$	-	10^{-4}	-	K^{-1}
Oscillator Voltage Dependency	$\Delta f/f / \Delta V_P$	$V_P = 10V$ to $30V$	-	4×10^4	-	K^{-1}
Synchronizing Ratio	f_O / f_{sync}		1:2.9	1:3	-	

Pin Connection Diagram
(Front View)

