

QM200HC-M

HIGH POWER SWITCHING USE
NON-INSULATED TYPE

QM200HC-M






- **IC** Collector current **200A**
- **VCEX** Collector-emitter voltage **350V**
- **hFE** DC current gain **100**
- **Non-Insulated Type**

APPLICATION

Robotics, Welders, Forklifts, Golf cart

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



QM200HC-M

**HIGH POWER SWITCHING USE
NON-INSULATED TYPE**

ABSOLUTE MAXIMUM RATINGS (T_j=25°C, unless otherwise noted)

Symbol	Parameter	Conditions	Ratings	Unit
V _{CEX(SUS)}	Collector-emitter voltage	I _C =1A, V _{EB} =2V	350	V
V _{CEX}	Collector-emitter voltage	V _{EB} =2V	350	V
V _{CBO}	Collector-base voltage	Emitter open	400	V
V _{EBO}	Emitter-base voltage	Collector open	10	V
I _C	Collector current	DC	200	A
-I _C	Collector reverse current	DC (forward diode current)	200	A
P _C	Collector dissipation	T _C =25°C	830	W
I _B	Base current	DC	6	A
-I _{CSM}	Surge collector reverse current (forward diode current)	Peak value of one cycle of 60Hz (half wave)	2000	A
T _j	Junction temperature		-40~+150	°C
T _{stg}	Storage temperature		-40~+125	°C
V _{iso}	Isolation voltage	Charged part to case, AC for 1 minute	—	V
—	Mounting torque	B(E) terminal screw M4	0.98~1.47	N·m
			10~15	kg·cm
		BX terminal screw M4	0.98~1.47	N·m
			10~15	kg·cm
		Main terminal screw M6	1.96~2.94	N·m
			20~30	kg·cm
—	Weight	Typical value	1.47~1.96	N·m
			15~20	kg·cm

ELECTRICAL CHARACTERISTICS (T_j=25°C, unless otherwise noted)


Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
I _{CEX}	Collector cutoff current	V _{CE} =350V, V _{EB} =2V	—	—	1.0	mA
I _{CBO}	Collector cutoff current	V _{CB} =400V, Emitter open	—	—	1.0	mA
I _{EBO}	Emitter cutoff current	V _{EB} =10V	—	—	400	mA
V _{CE(sat)}	Collector-emitter saturation voltage	I _C =200A, I _B =2A	—	—	2.0	V
V _{BE(sat)}	Base-emitter saturation voltage		—	—	2.5	V
-V _{CEO}	Collector-emitter reverse voltage	-I _C =200A (diode forward voltage)	—	—	1.5	V
h _{FE}	DC current gain	I _C =200A, V _{CE} =2V	100	—	—	—
t _{on}	Switching time	V _{CC} =200V, I _C =200A, I _{B1} =-I _{B2} =4A	—	—	2.0	μs
t _s			—	—	10	μs
t _f			—	—	3.0	μs
R _{th(j-c) Q}			Thermal resistance (junction to case)	Transistor part	—	—
R _{th(j-c) R}	Diode part	—		—	0.25	°C/W
R _{th(c-f)}	Contact thermal resistance (case to fin)	Conductive grease applied	—	—	0.07	°C/W

QM200HC-M


HIGH POWER SWITCHING USE
NON-INSULATED TYPE

PERFORMANCE CURVES


COMMON EMITTER OUTPUT CHARACTERISTICS (TYPICAL)




DC CURRENT GAIN VS. COLLECTOR CURRENT (TYPICAL)




COMMON EMITTER INPUT CHARACTERISTIC (TYPICAL)




SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE (TYPICAL)




SWITCHING TIME VS. COLLECTOR CURRENT (TYPICAL)




QM200HC-M

HIGH POWER SWITCHING USE
NON-INSULATED TYPE


SWITCHING TIME VS. BASE CURRENT (TYPICAL)




REVERSE BIAS SAFE OPERATING AREA




FORWARD BIAS SAFE OPERATING AREA




DERATING FACTOR OF F. B. S. O. A.



TRANSIENT THERMAL IMPEDANCE CHARACTERISTIC (TRANSISTOR)




REVERSE COLLECTOR CURRENT VS. COLLECTOR-EMITTER REVERSE VOLTAGE (DIODE FORWARD CHARACTERISTICS) (TYPICAL)




QM200HC-M

HIGH POWER SWITCHING USE
NON-INSULATED TYPE

**RATED SURGE COLLECTOR REVERSE CURRENT
(DIODE FORWARD SURGE CURRENT)**



**REVERSE RECOVERY CHARACTERISTICS
OF FREE-WHEEL DIODE (TYPICAL)**



**TRANSIENT THERMAL IMPEDANCE
CHARACTERISTIC (DIODE)**

