



DC COMPONENTS CO., LTD.

RECTIFIER SPECIALISTS

**SK12
THRU
SK18**

TECHNICAL SPECIFICATIONS OF SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE - 20 to 80 Volts

CURRENT - 1.0 Ampere

FEATURES

- * Ideal for surface mounted applications
- * Low leakage current
- * Glass passivated junction

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- * Polarity: As marked
- * Mounting position: Any
- * Weight: 0.093 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS



Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%.



SMB (DO-214AA)



Dimensions in inches and (millimeters)

		SYMBOL	SK12	SK13	SK14	SK15	SK16	SK18	UNITS
Maximum Recurrent Peak Reverse Voltage		V _{RRM}	20	30	40	50	60	80	Volts
Maximum RMS Voltage		V _{RMS}	14	21	28	35	42	56	Volts
Maximum DC Blocking Voltage		V _{DC}	20	30	40	50	60	80	Volts
Maximum Average Forward Rectified Current at Derating Lead Temperature		I _O	1.0						Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)		I _{FSM}	50						Amps
Maximum Instantaneous Forward Voltage at 1.0A DC		V _F	0.55			0.70		0.85	Volts
Maximum DC Reverse Current	@ T _A = 25°C	I _R	1.0						mAmps
at Rated DC Blocking Voltage	@ T _A = 100°C		20						
Typical Thermal Resistance (Note 2)		R θJA	95						°C/W
Typical Junction Capacitance (Note 1)		C _J	130						pF
Operating Temperature Range		T _J	-65 to + 125						°C
Storage Temperature Range		T _{STG}	-65 to + 150						°C

- NOTES : 1. Thermal Resistance (Junction to Ambient).
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
3. P.C.B Mounted with 0.2X0.2*(5.0X5.0mm²) copper pad area.

RATING AND CHARACTERISTIC CURVES (SK12 THRU SK18)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3A - TYPICAL REVERSE CHARACTERISTICS




FIG. 3B - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL JUNCTION CAPACITANCE





FIG. 5 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT



DC COMPONENTS CO., LTD.