



Dual Enhancement Mode Field Effect Transistor (N and P Channel)

PRODUCT SUMMARY (N-Channel)		
V _{DSS}	I _D	R _{D(S)ON} (mΩ) Max
40V	5A	35 @ V _{GS} = 10V
		62 @ V _{GS} = 4.5V

PRODUCT SUMMARY (P-Channel)		
V _{DSS}	I _D	R _{D(S)ON} (mΩ) Max
-40V	-4A	47 @ V _{GS} = -10V
		65 @ V _{GS} = -4.5V

ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Parameter	Symbol	N-Channel	P-Channel	Unit	
Drain-Source Voltage	V _{DS}	40	-40	V	
Gate-Source Voltage	V _{GS}	±20	±20	V	
Drain Current-Continuous ^a @ T _a	25°C	I _D	5	-4	A
	70°C		4.2	-3.4	A
-Pulsed ^b	I _{DM}		20	-16	A
Drain-Source Diode Forward Current ^a	I _S	1.7	-1.7	A	
Maximum Power Dissipation ^a	T _a =25°C	P _D	2	W	
	T _a =70°C		1.44		
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55 to 150		°C	

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient ^a	R _{θJA}	62.5	°C/W
--	------------------	------	------

STM8450A

N-Channel ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D = 250µA	40			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 32V, V _{GS} = 0V		1		µA
Gate-Body Leakage	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V		±100		nA
ON CHARACTERISTICS ^b						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250µA	1.0	2.0	3.0	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D = 5A		25	35	m ohm
		V _{GS} = 4.5V, I _D = 4A		45	62	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = 5V, V _{GS} = 10V	15			A
Forward Transconductance	g _F	V _{DS} = 5V, I _D = 5A		8.5		S
DYNAMIC CHARACTERISTICS ^c						
Input Capacitance	C _{ISS}	V _{DS} = 10V, V _{GS} = 0V f = 1.0MHz		800	895	pF
Output Capacitance	C _{OSS}			150	168	pF
Reverse Transfer Capacitance	C _{RSS}			98	110	pF
Gate resistance	R _G	V _{GS} = 0V, V _{DS} = 0V, f = 1.0MHz		3		ohm
SWITCHING CHARACTERISTICS ^c						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = 15V I _D = 3 A V _{GS} = 10V R _{GEN} = 4.7 ohm		6.8	8	ns
Rise Time	t _r			8.4	9	ns
Turn-Off Delay Time	t _{D(OFF)}			16.6	18	ns
Fall Time	t _f			10.5	11	ns
Total Gate Charge	Q _G	V _{DS} = 24V, I _D = 5A, V _{GS} = 10V		15.3	18	nC
		V _{DS} = 24V, I _D = 5A, V _{GS} = 4.5V		7.7	9	nC
Gate-Source Charge	Q _{GS}	V _{DS} = 24V, I _D = 5 A V _{GS} = 4.5V		3	3.6	nC
Gate-Drain Charge	Q _{GD}			3.9	4.6	nC

STM8450A

P-Channel ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D = -250µA	-40			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -32V, V _{GS} = 0V		-1		µA
Gate-Body Leakage	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V		±100		nA
ON CHARACTERISTICS ^b						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250µA	-0.8	-1.5	-2.0	V
Drain-Source On-State Resistance	R _{DSON}	V _{GS} = -10V, I _D = -4A		37	47	m ohm
		V _{GS} = -4.5V, I _D = -3A		50	65	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = -5V, V _{GS} = -10V	20			A
Forward Transconductance	g _F	V _{DS} = -5V, I _D = -4A		9.5		S
DYNAMIC CHARACTERISTICS ^c						
Input Capacitance	C _{ISS}	V _{DS} = -10V, V _{GS} = 0V f = 1.0MHz		1090	1297	pF
Output Capacitance	C _{OSS}			205	240	pF
Reverse Transfer Capacitance	C _{RSS}			125	145	pF
Gate resistance	R _G	V _{GS} = 0V, V _{DS} = 0V, f = 1.0MHz		3.5		ohm
SWITCHING CHARACTERISTICS ^c						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = -15V I _D = -2.2A V _{GS} = -10V R _{GEN} = 4.7 ohm		8.7	10	ns
Rise Time	t _r			19.8	23	ns
Turn-Off Delay Time	t _{D(OFF)}			63.7	75	ns
Fall Time	t _f			26	30	ns
Total Gate Charge	Q _G	V _{DS} = -24V, I _D = -4A, V _{GS} = -10V		19.9	23	nC
		V _{DS} = -24V, I _D = -4A, V _{GS} = -4.5V		9.8	11	nC
Gate-Source Charge	Q _{GS}	V _{DS} = -24V, I _D = -4 A V _{GS} = -4.5V		2.8	3.2	nC
Gate-Drain Charge	Q _{GD}			4.2	4.9	nC

STM8450A

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0\text{V}, I_S = 1.7\text{A}$ $V_{GS} = 0\text{V}, I_S = -1.7\text{A}$	N-Ch P-Ch		0.8 -0.77	1.2 -1.2
						V

Notes

- a. Surface Mounted on FR4 Board, $t \leq 10\text{sec}$.
- b. Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2\%$.
- c. Guaranteed by design, not subject to production testing.

N-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Drain Current and Temperature

STM8450A

N-Channel




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 8. Body Diode Forward Voltage Variation with Source Current

STM8450A

P-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature

STM8450A

P-Channel




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. Transconductance Variation with Drain Current





Figure 8. Body Diode Forward Voltage Variation with Source Current


STM8450A

N-Channel



Q_g , Total Gate Charge (nC)


Figure 9. Gate Charge



V_{DS} , Drain-Source Voltage (V)


Figure 10. Maximum Safe Operating Area

P-Channel



Q_g , Total Gate Charge (nC)

Figure 9. Gate Charge



$-V_{DS}$, Body Diode Forward Voltage (V)

Figure 10. Maximum Safe Operating Area

STM8450A




Figure 11. S switching Test Circuit






Figure 12. S switching Waveforms

N-Channel





P-Channel



STM8450A

PACKAGE OUTLINE DIMENSIONS

SO-8




SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	4.98	0.189	0.196
E	3.81	3.99	0.150	0.157
H	5.79	6.20	0.228	0.244
L	0.41	1.27	0.016	0.050
θ	0°	8°	0°	8°

STM8450A

SO-8 Tape and Reel Data


SO-8 Carrier Tape



unit:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SOP 8N 150mil	6.40	5.20	2.10	$\phi 1.5$ (MIN)	$\phi 1.5$ $+ 0.1$ $- 0.0$	12.0 ± 0.3	1.75	5.5 ± 0.05	8.0	4.0	2.0 ± 0.05	0.3 ± 0.05

SO-8 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
12 mm	$\phi 330$	330 ± 1	62 ± 1.5	12.4 $+ 0.2$	16.8 $- 0.4$	$\phi 12.75$ $+ 0.15$	---	2.0 ± 0.15	---	---	---