

Tandem 600V HYPERFAST BOOST DIODE

MAJOR PRODUCTS CHARACTERISTICS


| | |
|----------------|--------|
| $I_{F(AV)}$ | 15 A |
| V_{RRM} | 600 V |
| $T_j(max)$ | 150 °C |
| $V_F(max)$ | 2.4 V |
| $I_{RM}(typ.)$ | 4.8 A |
| $t_{rr}(typ.)$ | 16 ns |

FEATURES AND BENEFITS

- ESPECIALLY SUITED AS BOOST DIODE IN CONTINUOUS MODE POWER FACTOR CORRECTORS AND HARD SWITCHING CONDITIONS
- DESIGNED FOR HIGH DI/DT OPERATION. HYPERFAST RECOVERY CURRENT TO COMPETE WITH SIC DEVICES. ALLOWS DOWNSIZING OF MOSFET AND HEATSINKS
- INTERNAL CERAMIC INSULATED DEVICES WITH EQUAL THERMAL CONDITIONS FOR BOTH 300V DIODES
- INSULATION (2500V_{RMS}) ALLOWS PLACEMENT ON SAME HEATSINK AS MOSFET AND FLEXIBLE HEATSINKING ON COMMON OR SEPARATE HEATSINK
- STATIC AND DYNAMIC EQUILIBRIUM OF INTERNAL DIODES ARE WARRANTED BY DESIGN
- PACKAGE CAPACITANCE: C=16pF

ABSOLUTE RATINGS (limiting values)

| Symbol | Parameter | | Value | Unit |
|--------------|--|---|----------|------|
| V_{RRM} | Repetitive peak reverse voltage | | 600 | V |
| $I_{F(RMS)}$ | RMS forward current | | 26 | A |
| I_{FSM} | Surge non repetitive forward current | $t_p = 10\text{ ms}$ sinusoidal | 130 | A |
| I_{peak} | Peak current waveform | $\delta = 0.15$ $T_c = 120^\circ\text{C}$ | 35 | A |
| T_{stg} | Storage temperature range | | -65 +150 | °C |
| T_j | Maximum operating junction temperature | | + 150 | °C |



DESCRIPTION

The TURBOSWITCH "H" is an ultra high performance diode composed of two 300V dice in series. TURBOSWITCH "H" family drastically cuts losses in the associated MOSFET when run at high di_F/dt .

STTH1506DPI

THERMAL AND POWER DATA

| Symbol | Parameter | Test conditions | Value | Unit |
|---------------|------------------|-----------------|-------|------|
| $R_{th(j-c)}$ | Junction to case | | 1.6 | °C/W |

STATIC ELECTRICAL CHARACTERISTICS (for both diodes)

| Symbol | Parameter | Tests Conditions | Min. | Typ. | Max. | Unit |
|------------|-------------------------|---------------------|---------------------------|------|------|---------------|
| I_R^* | Reverse leakage current | $V_R = V_{RRM}$ | $T_j = 25^\circ\text{C}$ | | 20 | μA |
| | | | $T_j = 125^\circ\text{C}$ | | 30 | |
| V_F^{**} | Forward voltage drop | $I_F = 15\text{ A}$ | $T_j = 25^\circ\text{C}$ | | 3.6 | V |
| | | | $T_j = 150^\circ\text{C}$ | | 1.95 | |

Pulse test: * $t_p = 100\text{ms}$, $\delta < 2\%$

** $t_p = 380\mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation:

$$P = 1.7 \times I_{F(AV)} + 0.047 \times I_{F(RMS)}^2$$

RECOVERY CHARACTERISTICS

| Symbol | Parameter | Tests Conditions | Min. | Typ. | Max. | Unit | |
|----------|----------------------------------|---|---------------------------|------|------|------|----|
| t_{rr} | Reverse recovery time | $I_F = 0.5\text{ A}$ $I_{rr} = 0.25\text{ A}$ $I_R = 1\text{ A}$ | $T_j = 25^\circ\text{C}$ | | 16 | ns | |
| | | $I_F = 1\text{ A}$ $di_F/dt = -50\text{ A}/\mu\text{s}$ $V_R = 30\text{ V}$ | | | | | 35 |
| I_{RM} | Reverse recovery current | $V_R = 400\text{ V}$ $I_F = 15\text{ A}$ $di_F/dt = -200\text{ A}/\mu\text{s}$ | $T_j = 125^\circ\text{C}$ | | 4.8 | 6.0 | A |
| S | Reverse recovery softness factor | | | | 0.4 | | - |
| Q_{rr} | Reverse recovery charges | | | | | 80 | |

TURN-ON SWITCHING CHARACTERISTICS

| Symbol | Parameter | Tests Conditions | Min. | Typ. | Max. | Unit |
|----------|--------------------------|--|------|------|------|------|
| t_{fr} | Forward recovery time | $I_F = 15\text{ A}$ $di_F/dt = 100\text{ A}/\mu\text{s}$, $V_{FR} = 1.1 \times V_{Fmax}$ | | | 200 | ns |
| V_{FP} | Forward recovery voltage | $I_F = 15\text{ A}$ $di_F/dt = 100\text{ A}/\mu\text{s}$ | | | 6 | V |

Fig. 1: Conduction losses versus average current.




Fig. 2: Forward voltage drop versus forward current.




Fig. 3: Relative variation of thermal impedance junction to case versus pulse duration.




Fig. 4: Peak reverse recovery current versus di_F/dt (typical values).




Fig. 5: Reverse recovery time versus di_F/dt (typical values).




Fig. 6: Reverse recovery charges versus di_F/dt (typical values).




Fig. 7: Softness factor versus di_F/dt (typical values).




Fig. 8: Relative variations of dynamic parameters versus junction temperature.




Fig. 9: Transient peak forward voltage versus di_F/dt (typical values).




Fig. 10: Forward recovery time versus di_F/dt (typical values).





Fig. 11: Junction capacitance versus reverse voltage applied (typical values).



PACKAGE MECHANICAL DATA
 DOP3I

| REF. | DIMENSIONS | | | |
|------|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.4 | 4.6 | 0.173 | 0.181 |
| B | 1.45 | 1.55 | 0.057 | 0.061 |
| C | 14.35 | 15.60 | 0.565 | 0.614 |
| D | 0.5 | 0.7 | 0.020 | 0.028 |
| E | 2.7 | 2.9 | 0.106 | 0.114 |
| F | 15.8 | 16.5 | 0.622 | 0.650 |
| G | 20.4 | 21.1 | 0.815 | 0.831 |
| H | 15.1 | 15.5 | 0.594 | 0.610 |
| K | 3.4 | 3.65 | 0.134 | 0.144 |
| L | 4.08 | 4.17 | 0.161 | 0.164 |
| N | 10.8 | 11.3 | 0.425 | 0.444 |
| P | 1.20 | 1.40 | 0.047 | 0.055 |
| R | 4.60 typ. | | 0.181 typ. | |

| Ordering code | Marking | Package | Weight | Base qty | Delivery mode |
|---------------|-------------|---------|---------|----------|---------------|
| STTH1506DPI | STTH1506DPI | DOP3I | 4.46 g. | 30 | Tube |

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.

All other names are the property of their respective owners.

© 2003 STMicroelectronics - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany -
 Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain -
 Sweden - Switzerland - United Kingdom - United States

www.st.com

