Unit: mm

TOSHIBA Diodes for Protecting against ESD Epitaxial Planar Type

DF3A6.8LFV

Product for Use Only as Protection against Electrostatic Discharge (ESD).

- * This product is for protection against electrostatic discharge (ESD) only and is not intended for any other usage, including without limitation, the constant voltage diode application.
- The mounting of two devices in an ultra-compact package enables a reduction in the number of parts and in the mounting cost.
- Low terminal capacitance: C_T = 6.0 pF (typ.)

Absolute Maximum Ratings (Ta = 25°C)

Characteristic	Symbol	Rating	Unit
Power dissipation	Р	150*	mW
Junction temperature	Tj	150	°C
Storage temperature range	T _{stg}	-55~150	°C


Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.

1.2±0.05
0.8±0.06
0.8±0.06
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0±2.0
0.0

Weight: 1.5 mg (typ.)

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

*: Mounted on an FR4 board (25.4 mm × 25.4 mm × 1.6 mmt)



Electrical Characteristics (Ta = 25°C)

Characteristic	Symbol	Test Condition	Min	Тур.	Max	Unit
Zener voltage	VZ	$I_Z = 5 \text{ mA}$	6.5	6.8	7.1	V
Dynamic impedance	Z _Z	I _Z = 5 mA	_	_	50	Ω
Reverse current	I _R	V _R = 5 V	_	_	0.5	μА
Terminal capacitance (between cathode and anode)	C _T	V _R = 0 V, f = 1 MHz	_	6.0	_	pF

Guaranteed Level of ESD Immunity

Test Condition	ESD Immunity Level
IEC61000-4-2 (Contact discharge)	± 8 kV


Criterion: No damage to device elements


Marking

Equivalent Circuit (top view)









RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in his document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- Please contact your sales representative for product-by-product details in this document regarding RoHS
 compatibility. Please use these products in this document in compliance with all applicable laws and regulations
 that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses
 occurring as a result of noncompliance with applicable laws and regulations.