



A5A:1650.XX

VOLTAGE RATINGS

Part Number	V _{RRM} , V _R (V) Max. rep. peak reverse voltage		V _{RSM} , V _R (V) Max. non-rep. peak reverse voltage
	T _J = 0 to 180°C	T _J = -40 to 0°C	T _J = 25 to 180°C
A5A:1650.02	200	200	300
A5A:1650.04	400	400	500
A5A:1650.06	600	600	700
A5A:1650.08	800	800	900
A5A:1650.10	1000	1000	1100
A5A:1650.12	1200	1200	1300

MAXIMUM ALLOWABLE RATINGS

PARAMETER	VALUE	UNITS	NOTES
T _J Junction Temperature	-40 to 180	°C	-
T _{stg} Storage Temperature	-40 to 180	°C	-
I _{F(AV)} Max. Av. current @ Max. T _C	1300	A	180° half sine wave
	125	°C	
I _{F(RMS)} Nom. RMS current	2625	A	-
I _{FSM} Max. Peak non-rep. surge current	18.0	kA	50 Hz half cycle sine wave Initial T _J = 180°C, rated V _{RRM}
	18.9		60 Hz half cycle sine wave applied after surge.
	21.5		50 Hz half cycle sine wave Initial T _J = 180°C, no voltage
	22.5		60 Hz half cycle sine wave applied after surge.
I ² t Max. I ² t capability	1630	kA ² s	t = 10ms Initial T _J = 180°C, rated V _{RRM}
	1490		t = 8.3 ms applied after surge.
	2310		t = 10ms Initial T _J = 180°C, no voltage
	2110		t = 8.3 ms applied after surge.
I ² t ^{1/2} Max. I ² t ^{1/2} capability	23100	kA ² s ^{1/2}	Initial T _J = 180°C, no voltage applied after surge. I ² t for time t _x = I ² t ^{1/2} * t _x ^{1/2} . (0.1 < t _x < 10ms).
F Mounting Force	1550	N.m	-



A5A:1650.XX

CHARACTERISTICS

PARAMETER	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
V_{FM} Peak forward voltage	---	1.45	1.63	V	Initial $T_J = 25^\circ\text{C}$, 50-60Hz half sine, $I_{peak} = 4084\text{A}$.
$V_{F(TO)1}$ Low-level threshold	---	---	0.794	V	$T_J = 180^\circ\text{C}$
$V_{F(TO)2}$ High-level threshold	---	---	0.857		$\text{Av. power} = V_{F(TO)} * I_{F(AV)} + r_F * [I_{F(RMS)}]^2$
r_F Low-level resistance	---	---	0.195	m	Use low values for $I_{FM} < I_{F(AV)}$
r_F High-level resistance	---	---	0.170		
I_{RM} Peak reverse current	---	30	60	mA	$T_J = 180^\circ\text{C}$. Max. rated V_{RRM}
R_{thJC} Thermal resistance, junction-to-case	---	---	0.035	°C/W	DC operation, double side
	---	---	0.039	°C/W	180° sine wave, double side
	---	---	0.040	°C/W	120° rectangular wave, double side
R_{thCS} Thermal resistance, case-to-sink	---	---	0.015	°C/W	Mtg. Surface smooth, flat and greased. Double side cooled.
wt Weight	---	255(9)	---	g(oz.)	---
Case Style	TO-200AC				---




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics



A5A:1650.XX



Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Forward Voltage Drop Characteristics




Fig. 6 - Transient Thermal Impedance Characteristics



AEGIS
SEMICONDUTORES LTDA.

A5A:1650.XX

TO-200AC





Fig. 7 - Outline Characteristics