




P-Channel 40-V (D-S), 175°C MOSFET


PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
-40	0.015 @ $V_{GS} = -10$ V	-50
	0.023 @ $V_{GS} = -4.5$ V	-45

175°C Rated
Maximum Junction Temperature
TrenchFET®
Power MOSFETs



Order Number:
SUD50P04-15

Drain Connected to Tab



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	-40	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ^b	$T_C = 25^\circ\text{C}$	I_D	-50	A
	$T_C = 100^\circ\text{C}$		-40	
Pulsed Drain Current		I_{DM}	-150	
Continuous Source Current (Diode Conduction)		I_S	-50	
Maximum Power Dissipation ^b	$T_C = 25^\circ\text{C}$	P_D	100 ^b	W
	$T_A = 25^\circ\text{C}$		3 ^a	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^a	$t \leq 10$ sec.	R_{thJA}	15	18	$^\circ\text{C/W}$
	Steady State		40	50	
Maximum Junction-to-Case		R_{thJC}	1.2	1.5	

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
- b. See SOA curve for voltage derating.









SPECIFICATIONS (T_J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -250 μA	-40			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-1.0			
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -40 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -40 V, V _{GS} = 0 V, T _J = 125 °C			-50	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = -5 V, V _{GS} = -10 V	-120			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = -10 V, I _D = -30 A		0.012	0.015	Ω
		V _{GS} = -10 V, I _D = -30 A, T _J = 125 °C			0.024	
		V _{GS} = -4.5 V, I _D = -20 A		0.018	0.023	
Forward Transconductance ^a	g _{fs}	V _{DS} = -15 V, I _D = -30 A	20			S
Dynamic^b						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = -25 V, f = 1 MHz		5400		pF
Output Capacitance	C _{oss}			640		
Reverse Transfer Capacitance	C _{rss}			300		
Total Gate Charge ^c	Q _g	V _{DS} = -20 V, V _{GS} = -10 V, I _D = -50 A		85	130	nC
Gate-Source Charge ^c	Q _{gs}			25		
Gate-Drain Charge ^c	Q _{gd}			15		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = -20 V, R _L = 0.4 Ω I _D ≅ -50 A, V _{GEN} = -10 V, R _G = 2.5 Ω		15	25	ns
Rise Time ^c	t _r			380	580	
Turn-Off Delay Time ^c	t _{d(off)}			75	115	
Fall Time ^c	t _f			140	210	
Source-Drain Diode Ratings and Characteristic (T_C = 25 °C)						
Pulsed Current	I _{SM}				-150	A
Diode Forward Voltage ^a	V _{SD}	I _F = -50 A, V _{GS} = 0 V		-1.2	-1.5	V
Source-Drain Reverse Recovery Time	t _{rr}	I _F = -50 A, di/dt = 100 A/μs		40	80	ns

Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.
- c. Independent of operating temperature.





TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)








TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



THERMAL RATINGS





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.