

DEC

SR102 THRU SR1100


CURRENT 1.0Ampere
VOLTAGE 20 to 100 Volts

Features

- Plastic Package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction, majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss, high efficiency
- High current capability, Low forward voltage drop
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- High temperature soldering guaranteed :
250 °C/10 seconds at terminals,
0.375" (9.5mm) lead length, 5lbs. (2.3Kg) tension

Mechanical Data

- Case : JEDEC DO-41 molded plastic body
- Terminals : Plated axial leads, solderable per MIL-STD-750, Method 2026
- Polarity : Color band denotes cathode end
- Mounting Position : Any
- Weight : 0.012 ounce, 0.33 gram



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

(Ratings at 25 °C ambient temperature unless otherwise specified, single phase, half wave, resistive or inductive load. For capacitive load, derate by 20%)

	Symbols	SR102	SR103	SR104	SR105	SR106	SR108	SR1100	Units			
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	Volts			
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	Volts			
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	Volts			
Maximum average forward rectified current 0.375"(9.5mm) lead length(see Fig. 1)	I _(AV)	1.0						Amp				
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	40.0						Amps				
Maximum instantaneous forward voltage at 1.0A (Note 1)	V _F	0.55		0.70		0.75	0.83	Volts				
Maximum instantaneous reverse current at rated DC blocking voltage (Note1)	TA=25 °C	I _R	1.0						mA			
	TA=100 °C		10									
Typical junction capacitance (Note 3)	C _J	110						PF				
Typical thermal resistance (Note 2)	R _{θJA} R _{θJL}	50.0 15.0						°C/W				
Operating junction temperature range	T _J	-65 to +125		-65 to +150		°C						
Storage temperature range	T _{STG}	-65 to +150						°C				

Notes:

(1) Pulse test: 300μS pulse width, 1% duty cycle

(2) Thermal resistance from junction to ambient P.C.B. mounted, with 1.5X1.5"(38X38mm) copper pads

(3) Measured 1.0MHz and reverse voltage of 4.0 volts

DEC

RATINGS AND CHARACTERISTIC CURVES SR102 THRU SR1100

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.6-TYPICAL TRANSIENT THERMAL IMPEDANCE

