



AXIAL SILASTIC GUARD JUNCTION STANDARD RECTIFIER

1N5391G THRU 1N5399G


VOLTAGE RANGE 50 to 1000 Volts
CURRENT 1.5 Ampere

FEATURES

- Glass passivated chip junction
- Low forward voltage drop
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed
 260°C/10 secods, 0.375"(9.5mm) lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.012ounce, 0.39 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	1N 5391G	1N 5392G	1N 5393G	1N 5394G	1N 5395G	1N 5396G	1N 5397G	1N 5398G	1N 5399G	UNIT	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	300	400	500	600	800	1000	Volts	
Maximum RMS Voltage	V_{RMS}	35	70	140	210	280	350	420	560	700	Volts	
Maximum DC Blocking Voltage	V_{DC}	50	100	200	300	400	500	600	800	1000	Volts	
Maximum Average Forward Rectified Current 0.375"(9.5mm) lead length at $T_A=75^\circ\text{C}$	$I_{(AV)}$	1.5									Amps	
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}	50									Amps	
Maximum Instantaneous Forward Voltage at 1.5A	V_F	1.1									Volts	
Maximum DC Reverse Current at rated DC blocking Voltage at	$T_A = 25^\circ\text{C}$										5.0	μA
	$T_A = 125^\circ\text{C}$											
Maximum Full Load Reverse Current, full cycle Average 0.375(9.5mm) lead length at $T_L=75^\circ\text{C}$	$I_{R(AV)}$	30									μA	
Typical Junction Capacitance (NOTE 1)	C_J	20									pF	
Typical Thermal Resistance (NOTE 2)	$R_{\theta JA}$	50									$^\circ\text{C}/\text{W}$	
Operating Temperature Range	T_J	(-55 to +150)									$^\circ\text{C}$	
Storage Temperature Range	T_{STG}	(-55 to +150)									$^\circ\text{C}$	

Notes:

1. Measured at 1.0MHz and applied reverse voltage of 4.0 Volts.
2. Thermal Resistance from Junction to Ambient at. 375"(9.5mm) lead length, P.C. board mounted.



AXIAL SILASTIC GUARD JUNCTION STANDARD RECTIFIER

1N5391G THRU 1N5399G

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 1.5 Ampere

RATING AND CHARACTERISTIC CURVES 1N5391G THRU 1N5399G

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

