

## FEATURES AND SPECIFICATIONS



## Application Tooling Manual PPHLS

**19286-0117**

### Putt Pump Hydraulic Head Crimper for Insulated and Non-Insulated Terminals and Splices

#### Features and Benefits

- Multiple crimping dies available for a wide wire range, which provides production flexibility
- Crimping dies are easily and quickly interchanged to reduce production downtime
- Lightweight system that allows the tool to be moved and stored easily

#### Specifications

Pneumatic: Supply Pressure –100 PSI  
Air Pressure –125 PSI max.  
Cycle Time: 15 seconds



## ORDERING INFORMATION

Order No.	Wire Gauge (AWG)	Die Set for the PPDH 19286-0117	
		VersaKrimp™ Terminals and Splices	NylaKrimp™/InsulKrimp™ Terminals and Splices
19286-0117	8	19290-0001	19289-0001
19286-0117	6	19290-0004	19289-0004
19286-0117	4	19290-0007	19289-0007
19286-0117	2	19290-0010	19289-0010
19286-0117	1		
19286-0117	1/0	19290-0011	19289-0011
19286-0117	2/0	19290-0012	19289-0025
19286-0117	3/0	19290-0028	19289-0028
19286-0117	4/0	19290-0031	19289-0031



Bringing People & Technology Together, Worldwide<sup>SM</sup>

**Americas Headquarters**  
Lisle, Illinois 60532 U.S.A.  
1-800-78MOLEX  
amerinfo@molex.com

**Far East North Headquarters**  
Yamato, Kanagawa, Japan  
81-462-65-2324  
feninfo@molex.com

**Far East South Headquarters**  
Jurong, Singapore  
65-6-268-6868  
fesinfo@molex.com

**European Headquarters**  
Munich, Germany  
49-89-413092-0  
eurinfo@molex.com

**Corporate Headquarters**  
2222 Wellington Ct.  
Lisle, IL 60532 U.S.A.  
630-969-4550  
Fax: 630-969-1352

Visit our website at [www.molex.com](http://www.molex.com)