




YUXIANG

www.magnet-tech.com

China Professional Ferrite Core Supplier

ET SERIES



Introduce of ET core

Ferrite cores consisted of stacks of laminations; patterns cut or stamped out of thin sheets of electrical steels. Most applications required a lamination pattern (or patterns) that would form a closed magnetic loop when assembled together. The shape of ET core is closed magnetic loop, which unlike other E shape cores. When apply with electronic parts, the ET core possess high efficiency, low leakage inductance.

Application of ET core

Mn-Zn high permeability ET cores can be widely used as Balance cores, cable cores, Pulse Transformer core to application in Electronic parts for Green Illumination Project and Common-Mode Choke, etc.

Type	Dimensions(mm)					
	A	B	C	D	E	F
ET20	20.1±0.5	20.1±0.5	4.0±0.2	4.4±0.2	2.0±0.2	2.0±0.2
ET24	24.2±0.5	24.2±0.5	4.0±0.2	4.0±0.3	2.4±0.2	2.0±0.2
ET28	28.7±0.5	28.7±0.5	5.0±0.3	5.0±0.3	2.9±0.2	2.9±0.2
ET35	53.3±0.6	35.3±0.6	7.5±0.3	7.5±0.3	4.0±0.2	4.0±0.2

Type	Core parameter		weight (g/pr.)	Al(nH/N ²)±25%	
	Ae (mm ²)	Ie (mm)		Fs7 +40% -25%	Fs10(±25%)
ET20	18	50.6	4.6	3100	4300
ET24	18	61	5.6	2600	3600
ET28	27	71.4	10.5	3550	4800
ET35	56	86.7	26	6000	8400

Copyright 2005 YUXIANG Magnetic Materials Ind. Co.,Ltd.All Rights Reserved.

Add: 16F1,Jinyuan building,NO.57,hubin S.Rd.,Xiamen,China.361004

Tel : (86)592 2225286 (86)592 2219816 (86)592 2217138 Fax: (86)592 2207122

Email : magnetcom@gmail.com sales@magnet-tech.com