



## 2-channel EMI Filter with ESD-Protection

### Features

- Ultra compact LLP75 package
- 2-channel EMI-Filter + ESD-protection
- Low leakage current
- Line resistance of 50 Ohms
- Typical cut-off frequency 100 MHz
- ESD protection to **IEC 61000-4-2 ± 30 kV (Air)**
- ESD protection to **IEC 61000-4-2 ± 30 kV (Contact)**
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE2002/96/EC



### Marking:



Square = Pin 1 marking

“T1” = Type Code for VEMI255A-HS3

SD = Date Code (Example only)

### Mechanical Data

**Case:** LLP75-6A (plastic package).

Non magnetic

**Molding Compound Flammability Rating:**

UL 94 V-0

**Terminals:** High temperature soldering guaranteed:

260 °C/10 sec. at terminals

**Weight:** 5 mg

**Packaging Codes/Options:**

GS18 = 10 k per 13" reel (8 mm tape), 10 k/box

GS08 = 3 k per 7" reel (8 mm tape), 15 k/box

### Absolute Maximum Ratings

Ratings at 25 °C, ambient temperature unless otherwise specified

Parameter	Symbol	Value	Unit
ESD Air Discharge per IEC 61000-4-2	$V_{ESD}$	30	kV
ESD Contact Discharge per IEC 61000-4-2	$V_{ESD}$	30	kV

### Thermal Characteristics

Ratings at 25 °C, ambient temperature unless otherwise specified

Parameter	Symbol	Value	Unit
Operating Temperature	$T_J$	- 40 to + 125	°C
Storage Temperature	$T_{STG}$	- 55 to + 150	°C

### Electrical Characteristics

( $T_A = 25\text{ °C}$  unless otherwise specified)

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Reverse Stand-Off Voltage	at $I_R = 1\ \mu\text{A}$ each Input to Pin 2	$V_{RWM}$	5			V
Max. Reverse current	at $V_R = 5\ \text{V}$ each Input to Pin 2	$I_R$			1	$\mu\text{A}$

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Max. Output Clamping voltage	at $I_{PP} = 4$ A each Input to Pin 2 Acc. IEC 61000-4-5 measured at output pin	$V_C$			8	V
Max. Forward Clamping voltage	at $I_F = 4$ A each Input to Pin 2 Acc. IEC 61000-4-5	$V_F$			4.5	V
Max. Peak pulse current	each Input to Pin 2 Acc. IEC 61000-4-5	$I_{PPM}$	- 4		4	A
Min. Reverse Breakdown Voltage	each Input to Pin 2 at $I_R = 1$ mA	$V_{BR}$	6			V
Input Capacitance	each Input to Pin 2; output not connected; $V_{IN} = 0$ V ; $f = 1$ MHz	$C_{IN}$		60		pF
ESD-Immunity	10 pulses, both polarities Acc. IEC 6100-4-2 device not damaged	$V_{ESD}$		$\pm 30$ kV		V
Cut-off Frequency	Measured in a 50 Ohm system	$f_{3dB}$		100		MHz
Line Resistance	Measure between input and output; Pin 2 = not connecte; $I_S = 10$ mA	$R_S$		50		$\Omega$




Figure 1. 8/20µs Peak Pulse Current wave form  
acc. IEC 61000-4-5




Figure 3. Typical Capacitance  $C_{IN}$  vs. Reverse Voltage  $V_{IN}$




Figure 2. Typical small signal transmission (S21) @  $Z_0 = 50$  Ohm




Figure 4. Typical Input Voltage  $V_{IN}$  vs. Input Current  $I_{IN}$






Figure 5. Typical Clamping Voltage vs. Peak Pulse Current  $I_{PP}$

### Application Note:

- a) With the **VEMI255A-HS3** 2 different signal or data lines can be filtered and clamped to ground. Due to the different clamping levels in forward and reverse direction the clamping behavior is **B**idirectional and **A**symmetric (**BiAs**).



19500




19420

The 2 independent EMI-Filter are placed between


Pin 1 & Pin 6, and  
Pin 3 & Pin 4

They all are connected to the common ground Pin no. 2. Pin no. 5 is not connected. Each filter is symmetrical so that all ports (Pin 1, 3, 4 & 6) can be used as Input or Output.



19421


Circuit diagram of one EMI-Filter-Channel



19467

Each filter is symmetrical so that both ports can be used as Input or Output.

## Package dimensions in mm (inches)



18058

### Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



### Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.