

CliQ Din Rail Power Supply

24V 480W 1 Phase

DRP024V480W1AA



DRP024V480W1AA

480Watts

Total Power: 480Watts
Input Voltage: 85-264Vac
of Output: Single

Model number	DRP024V480W1AA
Reference no.	EOE13010007
OUTPUT (DC)	
Output power	480W
Output voltage range	22 - 28V
Output current	20A
Residual ripple/peak switching (20MHz) (@ nominal values)	< 50mV / < 240mVpp
Mains buffering at nominal load (typ.)	> 20ms @ 115Vac & 230Vac
Line regulation	< 0.5% typ. (@ 85 - 264Vac input, 100% load)
Load regulation	< 1% typ. (with rated input, 0 - 100% load)
INPUT (AC)	
Input voltage range	85 - 264Vac (DC input range 120 - 375Vdc)
Input frequency	47 - 63Hz
Nominal current	5.7A @ 115Vac, 2.8A @ 230Vac
Efficiency	> 86% typ.
Power factor	Conform to EN61000-3-2 STD
Inrush current limitation I ² t (+25°C) typ.	No damage at I ² t ratings for all I/P devices shall not exceed their rating
Leakage current	< 1mA

MECHANICAL DESIGN	
Case cover	Aluminium (Al5052)
Dimensions (L x W x H)	121mm x 160mm x 118.5mm
Unit weight / box	1.800kg
MTBF	> 300,000 hrs
Noise	Sound pressure level (SPL) < 40dBA
Cooling	Convection
Input terminal	M4 x 3
Output terminal	M4 x 2 (2 pcs.)
Mounting rail	Standard TS35 mounting rail
Shock proof	IEC60068-2-27
Vibration	IEC60068-2-6
Protection structure	EN60950 meet IPX0


Special Features

- Ease of wire connection to terminals
- Compact design for easy handling
- Overload protection
- Overvoltage protection
- Thermal protection
- Power boost 150% for 3 seconds
- Expected life time : 10 years
- Shock proof IEC60068-2-27
- Vibration IEC60068-2-6
- Cooling : Convection
- Operating Humidity : < 95%
- Redundancy : Yes
(with external ORing diode)
- RoHS compliant



CliQ Din Rail Power Supply 24V 480W 1 Phase DRP024V480W1AA

MECHANICAL DRAWING



Delta Electronics (Thailand)
Public Company Limited
909 Moo 4, E.P.Z.,
Bangpoo Industrial Estate,
Tambon Prakasa, Amphur
Muang Samutprakarn,
Samutprakarn 10280, Thailand
Tel: +662 709 2800
Fax: +662 709 2827
E-mail: VL@delta.co.th
www.deltaenergysystems.com

SAFETY / ENVIRONMENTAL

EMC / Emissions	Class B / EN55022, CISPR22, Class B; FCC Tilte 47; EN61204-3 (Class B on AC & Class A on DC side), EN55022:2006 Class B, EN61000-3-2:2006, EN61000-3-3:1995/ A1:2001/A2:2005
Immunity	EN55024:1998/A1:2001/A2:2003
Safety standard	UL508, CSA C22.2 No.107.1-01, UL60950-1, CSA C22.2 No.60950-1, IEC60950-1, EN60950-1, EN50178, IEC62103 and IEC60204-1
Voltage dips	Conform to EN61000-4-11
Galvanic isolation	Input to output: 4KVac Input to ground: 1.5KVac Output to ground: 1.5KVac
Operating ambient temperature	-20°C ~ 75°C *
Storage temperature	-25°C ~ 85°C
Operating humidity	< 95%
Note (*)	* Operating amb. > 50°C derate power by 2.5% / °C