

## 500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators




### Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Parameter	Value	Units
Power Dissipation	500	mW
Storage Temperature Range	-65 to +175	$^\circ\text{C}$
Operating Junction Temperature	+175	$^\circ\text{C}$

These ratings are limiting values above which the serviceability of the diode may be impaired.


### DEVICE MARKING DIAGRAM



L : Logo  
 Device Code : TCZXxxxT  
 VZ Tolerance (T) : A, B, C or D

### Specification Features:

- Zener Voltage Range 2.0 to 39 Volts
- DO-35 Package (JEDEC)
- Through-Hole Device Type Mounting
- Hermetically Sealed Glass
- Compression Bonded Construction
- All External Surfaces Are Corrosion Resistant And Leads Are Readily Solderable
- RoHS Compliant
- Solder Hot Dip Tin (Sn) Terminal Finish
- Cathode Indicated By Polarity Band



### ELECTRICAL SYMBOL

### Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Device Type	VZ Tolerance	VZ@IZT			Izt (mA)	Zzt@Izt (Ohms) Max	Zzk@Izk (Ohms) Max	Izk (mA)	I <sub>R</sub> @V <sub>R</sub> (uA) Max	V <sub>R</sub> (V)
		Min	Nom	Max						
TCZX2V0	A	1.880	1.990	2.100	5	100	1000	0.5	120	0.5
	B	2.020	2.110	2.200						
TCZX2V2	A	2.120	2.210	2.300	5	100	1000	0.5	100	0.7
	B	2.220	2.315	2.410						
TCZX2V4	A	2.330	2.425	2.520	5	100	1000	0.5	120	1.0
	B	2.430	2.530	2.630						
TCZX2V7	A	2.540	2.645	2.750	5	110	1000	0.5	100	1.0
	B	2.690	2.800	2.910						
TCZX3V0	A	2.850	2.960	3.070	5	120	1000	0.5	50	1.0
	B	3.010	3.115	3.220						
TCZX3V3	A	3.160	3.270	3.380	5	120	1000	0.5	20	1.0
	B	3.320	3.425	3.530						
TCZX3V6	A	3.455	3.575	3.695	5	100	1000	1	10	1.0
	B	3.600	3.723	3.845						
TCZX3V9	A	3.740	3.875	4.010	5	100	1000	1	5	1.0
	B	3.890	4.025	4.160						
TCZX4V3	A	4.040	4.165	4.290	5	100	1000	1	5	1.0
	B	4.170	4.300	4.430						
	C	4.300	4.435	4.570						
TCZX4V7	A	4.44	4.56	4.68	5	80	900	1	5	1.0
	B	4.55	4.68	4.80						
	C	4.68	4.81	4.93						
TCZX5V1	A	4.81	4.94	5.07	5	80	800	1	5	1.5
	B	4.94	5.07	5.20						
	C	5.09	5.23	5.37						

**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Device Type	T Tolerance	$V_Z@I_{ZT}$			$I_{ZT}$ (mA)	$Z_{ZT}@I_{ZT}$ (Ohms) Max	$Z_{ZK}@I_{ZK}$ (Ohms) Max	$I_{ZK}$ (mA)	$I_{R@V_R}$ (uA) Max	$V_R$ (V)
		Min	Nom	Max						
TCZX5V6	A	5.28	5.41	5.55	5	60	500	1	5	2.5
	B	5.45	5.59	5.73						
	C	5.61	5.76	5.91						
TCZX6V2	A	5.78	5.94	6.09	5	60	300	1	5	3.0
	B	5.96	6.12	6.27						
	C	6.12	6.28	6.44						
TCZX6V8	A	6.29	6.46	6.63	5	20	150	0.5	2	3.5
	B	6.49	6.66	6.83						
	C	6.66	6.84	7.01						
TCZX7V5	A	6.85	7.04	7.22	5	20	120	0.5	0.5	4.0
	B	7.07	7.26	7.45						
	C	7.29	7.48	7.67						
TCZX8V2	A	7.53	7.73	7.92	5	20	120	0.5	0.5	5.0
	B	7.78	7.99	8.19						
	C	8.03	8.24	8.45						
TCZX9V1	A	8.29	8.51	8.73	5	25	120	0.5	0.5	6.0
	B	8.57	8.79	9.01						
	C	8.83	9.07	9.30						
TCZX10V	A	9.12	9.36	9.59	5	30	120	0.5	0.2	7.0
	B	9.41	9.66	9.90						
	C	9.70	9.95	10.20						
	D	9.94	10.19	10.44						
TCZX11V	A	10.18	10.45	10.71	5	30	120	0.5	0.2	8.0
	B	10.50	10.78	11.05						
	C	10.82	11.10	11.38						
TCZX12V	A	11.13	11.42	11.71	5	30	110	0.5	0.2	9.0
	B	11.44	11.74	12.03						
	C	11.74	12.05	12.35						
TCZX13V	A	12.11	12.43	12.75	5	35	110	0.5	0.2	10
	B	12.55	12.88	13.21						
	C	12.99	13.33	13.66						
TCZX15V	A	13.44	13.79	14.13	5	40	110	0.5	0.2	11
	B	13.89	14.26	14.62						
	C	14.35	14.72	15.09						
TCZX16V	A	14.80	15.19	15.57	5	40	150	0.5	0.2	12
	B	15.25	15.65	16.04						
	C	15.69	16.10	16.51						
TCZX18V	A	16.22	16.64	17.06	5	45	150	0.5	0.2	13
	B	16.82	17.26	17.70						
	C	17.42	17.88	18.33						
TCZX20V	A	18.02	18.49	18.96	5	55	200	0.5	0.2	15
	B	18.63	19.11	19.59						
	C	19.23	19.73	20.22						
	D	19.72	20.22	20.72						
TCZX22V	A	20.15	21.68	21.20	5	30	200	0.5	0.2	17
	B	20.64	21.18	21.71						
	C	21.08	21.63	22.17						
	D	21.52	22.08	22.63						
TCZX24V	A	22.05	22.62	23.18	5	35	200	0.5	0.2	19
	B	22.61	23.19	23.77						
	C	23.12	23.72	24.31						
	D	23.63	24.24	24.85						
TCZX27V	A	24.26	24.89	25.52	5	45	250	0.5	0.2	21
	B	24.97	25.62	26.26						
	C	25.63	26.29	26.95						
	D	26.29	26.97	27.64						
TCZX30V	A	26.99	27.69	28.39	5	55	250	0.5	0.2	23
	B	27.70	28.42	29.13						
	C	28.36	29.09	29.82						
	D	29.02	29.77	30.51						

**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Device Type	T Tolerance	$V_z@I_{zt}$			$I_{zt}$ (mA)	$Z_{zt}@I_{zt}$ (Ohms) Max	$Z_{zk}@I_{zk}$ (Ohms) Max	$I_{zk}$ (mA)	$I_R@V_R$ ( $\mu\text{A}$ ) Max	$V_R$ (V)
		Min	Nom	Max						
TCZX33V	A	29.68	30.45	31.22	5	65	250	0.5	0.2	25
	B	30.32	31.10	31.88						
	C	30.90	31.70	32.50						
	D	31.49	32.30	33.11						
TCZX36V	A	32.14	32.97	33.79	5	75	250	0.5	0.2	27
	B	32.79	33.64	34.49						
	C	33.40	34.27	35.13						
	D	34.01	34.89	35.77						
TCZX39V	A	34.68	35.58	36.47	5	85	250	0.5	0.2	30
	B	35.36	36.28	37.19						
	C	36.00	36.93	37.85						
	D	36.63	37.58	38.52						

VF (forward voltage) = 1.2 V maximum @ IF = 200mA for all types

**Notes:**

**1. TOLERANCE AND VOLTAGE DESIGNATION**

The type numbers listed have zener voltage as shown

**2. SPECIALS AVAILABLE INCLUDE**

Nominal zener voltages between the voltages shown and tighter voltage, for detailed information on price, availability and delivery, contact you nearest Tak Cheong representative.

**3. ZENER VOLTAGE ( $V_z$ ) MEASUREMENT**


The zener voltage is measured under pulse conditions such that  $T_j$  is no more than  $2^\circ\text{C}$  above  $T_A$ .

**4. ZENER IMPEDANCE ( $Z_z$ ) DERIVATION**


Zener impedance is derived from the 60-cycle ac voltage, which results when an ac current having an RMS value equal to 10% of the dc zener current ( $I_{zt}$ ) is superimposed to  $I_{zt}$ .

**5. WHEN ORDERING, PLEASE SPECIFY TOLERANCE A, B, C OR D**


Typical Characteristics




**Figure 1. Power Dissipation vs Ambient Temperature**  
Valid provided leads at a distance of 0.8mm from case are kept at ambient temperature




**Figure 2. Total Capacitance**



**Figure 3. Differential Impedance vs. Zener Voltage**




**Figure 4. Forward Current vs. Forward Voltage**



**Figure 5. Reverse Current vs. Reverse Voltage**

Package Outline

Package	Case Outline					
DO-35						
	DIM	DO-35				
		Millimeters		Inches		
		Min	Max	Min	Max	
	A	0.46	0.55	0.018	0.022	
	B	3.05	5.08	0.120	0.200	
C	25.40	38.10	1.000	1.500		
D	1.53	2.28	0.060	0.090		

Notes:

1. All dimensions are within JEDEC standard.
2. DO35 polarity denoted by cathode band.

## **NOTICE**

The information presented in this document is for reference only. Tak Cheong reserves the right to make changes without notice for the specification of the products displayed herein.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Tak Cheong Semiconductor Co., Ltd., or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.takcheong.com>, or consult your nearest Tak Cheong's sales office for further assistance.