



5.00mm (.197") Pitch MX150™ Cable-Sealed 1-by-2 Connection System

34675 Male Connectors
34062 Female Receptacles

MX150 cable-sealed, 1-by-2 connectors are the latest addition to the high-performance MX150 connector system, providing a valuable space-saving solution for small-circuit applications

Molex's MX150 cable-sealed, 1-by-2 connection system was designed to meet the need for a rugged, environmentally sealed connector system supporting both low-level signal as well as power applications up to 22.0A for small circuit size applications where space is a premium.

The innovative cable-sealed connector family is based on the 1.50mm (.059") pitch ISO blade-type terminal system. The cable-seal design offers increased sealing reliability for a large range of SAE wire gauges (14 to 22) as well metric size wires, while offering low terminal-to-housing insertion forces, and high

terminal-to-housing retention forces in excess of USCAR-2 requirements. The cost-effective connector design features all-in-one plug and receptacle housings with a pre-assembled interfacial seal and terminal position assurance (TPA).

Optional connector position assurance (CPA) and clip slot features are offered to increase connector-to-connector and connector-to-vehicle retention during use. The MX150 cable-sealed connection system complements Molex's extensive MX150 product line. For additional information about this product visit: www.molex.com/ind/mx150.html.



1-by-2 Cable-Sealed Connection System



1-by-2 Cable-Sealed Connection System



Cable-Sealed Male and Female Terminals

Features and Benefits

- Compact 1.50mm (.059") terminal connector is capable of up to 22.0A continuous current
- Meets USCAR footprint: 150-S-002-1-Z01 to ensure mating with USCAR connector interfaces
- Glass-filled thermoplastic housing and pre-loaded Terminal Position Assurance (TPA) ensures crimped terminal leads are properly locked into the connector (TPA will not seat and the connector system will not latch if the terminal is not locked properly into position) and meets up to Temperature Class 3 performance
- Integral locking latch with secondary, pre-loaded connector position assurance (CPA) option ensures the connector system is properly latched (CPA will not move to final locking position if the connector is not latched)
- Optional clip slot aids in vehicle routing by offering an optional orientation clip attachment
- Audible and tactile clicks on insertion, extraction and mating feedback facilitates reliable mating, and terminal loading and removal

SPECIFICATIONS

Reference Information

Packaging:

Housings — Bulk Pack

Terminals — Reel

Mates With:

Series 34675 male connector to Series 34062 female receptacle

Use With:

Terminals: 34080 Male / 34083 Female

Designed in: Millimeters

Electrical

Voltage (max.): 500V

Current (max.): 22.0A

Contact Resistance: 10 milliohms max.

Dielectric Withstanding Voltage: 1500V AC

Isolation Resistance: 20 Megohms min.

Mechanical / Electrical / Sealing

Mating Force: Less than 45N (10.1 lb)

Unmating Force: Less than 45N (10.1 lb)

Connector Retention (Primary latch): 110N (24.7 lb) min.

Contact Retention to Housing: 90N (20.2 lb) min.

Contact Insertion Force Into Housing: 30N (6.7 lb) max.

Connector Audible Feedback: 7dB over ambient

Polarization Feature Effectiveness: 220N min.

FCLT (Class 3): 20 Milliohms max.

Durability (10 Cycles): 10 Milliohms max.

Thermal Shock (Class 3, 110cycles): 10 Milliohms max.

Sealing: (USCAR-2 Rev 4)

Pressure/Vacuum Immersion:

28kPa (4psi) 15 sec min.

Isolation resistance: 20 Megohms @ 500V DC min.

Physical

Housing: Nylon 6, 30% glass-filled

TPA: PBT, 30% glass-filled

Contact: C19025 Copper (Cu) Alloy

Plating:

Contact Area — Tin (Sn)

Underplating — Nickel (Si)

Operating Temperature: -40 to +125 °C

APPLICATIONS



5.00mm (.197") Pitch MX150™ Cable-Sealed 1-by-2 Connection System

- Automotive Vehicles
- Commercial Vehicles
- Recreational Vehicles
- Construction Equipment
- Marine Equipment

34675 Male Connectors
34062 Female Receptacles



ORDERING INFORMATION

Connector

Order No.	Component	Gender	Housing Features	Comment	Plant No. for Samples
34675-0002	Connector	Male	TPA	Polarization B, No Clip Slot	3109
34675-0003	Connector	Male	TPA	Polarization C, With Clip Slot	3109
34062-0022	Receptacle	Female	TPA and Interfacial Seal	Polarization B	3109
34062-0023	Receptacle	Female	TPA and Interfacial Seal	Polarization C	3109

Terminal

Order No.	Gender	Plating	Wire Size (AWG)	Plant No. for Samples
34080-0002	Male	Tin	18 to 20	3109
34083-2002	Female	Tin	18 to 20	3109

www.molex.com/ind/mx150.html

Americas Headquarters
Lisle, Illinois 60532 U.S.A.
1-800-78MOLEX
amerinfo@molex.com

Asia Pacific North Headquarters
Yamato, Kanagawa, Japan
81-46-265-2325
apninfo@molex.com

Asia Pacific South Headquarters
Jurong, Singapore
65-6268-6868
apsinfo@molex.com

European Headquarters
Munich, Germany
49-89-413092-0
eurinfo@molex.com

Corporate Headquarters
2222 Wellington Ct.
Lisle, IL 60532 U.S.A.
P: 630-969-4550 F: 630-969-1352