


## Glass Passivated Single-Phase Bridge Rectifier



Case Style WOG

### FEATURES

- UL recognition, file number E54214
- Ideal for printed circuit boards
- Typical  $I_R$  less than 0.5  $\mu$ A
- High case dielectric strength
- High surge current capability
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC


**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

General purpose use in ac-to-dc bridge full wave rectification for power supply, adapter, charger, lighting ballaster on consumers and home appliances applications.

### MECHANICAL DATA

**Case:** WOG

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Silver plated leads, solderable per J-STD-002 and JESD22-B102

E4 suffix for consumer grade

**Polarity:** As marked on body

| PRIMARY CHARACTERISTICS |                |
|-------------------------|----------------|
| $I_{F(AV)}$             | 2.0 A          |
| $V_{RRM}$               | 50 V to 1000 V |
| $I_{FSM}$               | 60 A           |
| $I_R$                   | 5.0 $\mu$ A    |
| $V_F$                   | 1.1 V          |
| $T_J$ max.              | 150 °C         |

| MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)                           |                |               |       |       |       |       |       |       |                  |
|---|----------------|---------------|-------|-------|-------|-------|-------|-------|------------------|
| PARAMETER   | SYMBOL         | 2W005G        | 2W01G | 2W02G | 2W04G | 2W06G | 2W08G | 2W10G | UNIT             |
| Maximum repetitive peak reverse voltage   | $V_{RRM}$      | 50            | 100   | 200   | 400   | 600   | 800   | 1000  | V                |
| Maximum RMS voltage   | $V_{RMS}$      | 35            | 70    | 140   | 280   | 420   | 560   | 700   | V                |
| Maximum DC blocking voltage   | $V_{DC}$       | 50            | 100   | 200   | 400   | 600   | 800   | 1000  | V                |
| Maximum average forward rectified current at 0.375" (9.5 mm) lead length (Fig. 1) | $I_{F(AV)}$    | 2.0           |       |       |       |       |       |       | A                |
| Peak forward surge current single sine-wave superimposed on rated load            | $I_{FSM}$      | 60            |       |       |       |       |       |       | A                |
| Rating for fusing ( $t < 8.3$ ms)   | $I^2t$         | 15            |       |       |       |       |       |       | A <sup>2</sup> s |
| Operating junction and storage temperature range                                  | $T_J, T_{STG}$ | - 55 to + 150 |       |       |       |       |       |       | °C               |

| ELECTRICAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |   |        |            |       |       |       |       |       |       |               |
|---|---|--------|------------|-------|-------|-------|-------|-------|-------|---------------|
| PARAMETER   | TEST CONDITIONS   | SYMBOL | 2W005G     | 2W01G | 2W02G | 2W04G | 2W06G | 2W08G | 2W10G | UNIT          |
| Maximum instantaneous forward voltage drop per diode                                  | 2.0 A   | $V_F$  | 1.1        |       |       |       |       |       |       | V             |
| Maximum DC reverse current at rated DC blocking voltage per diode                     | $T_A = 25\text{ }^\circ\text{C}$<br>$T_A = 125\text{ }^\circ\text{C}$ | $I_R$  | 5.0<br>500 |       |       |       |       |       |       | $\mu\text{A}$ |
| Typical junction capacitance per diode  | 4.0 V, 1 MHz  | $C_J$  | 40         |       |       |       | 20    |       |       | pF            |

| THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |                                    |          |       |       |       |       |       |       |                    |  |
|--|------------------------------------|----------|-------|-------|-------|-------|-------|-------|--------------------|--|
| PARAMETER  | SYMBOL                             | 2W005G   | 2W01G | 2W02G | 2W04G | 2W06G | 2W08G | 2W10G | UNIT               |  |
| Typical thermal resistance <sup>(1)</sup>  | $R_{\theta JA}$<br>$R_{\theta JL}$ | 40<br>15 |       |       |       |       |       |       | $^\circ\text{C/W}$ |  |

**Note:**

(1) Thermal resistance from junction to ambient and from junction to lead at 0.375" (9.5 mm) lead length P.C.B. mounting

| ORDERING INFORMATION (Example) |                 |                        |               |               |
|--------------------------------|-----------------|------------------------|---------------|---------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| 2W06G-E4/51                    | 1.12            | 51                     | 100           | Plastic bag   |

### RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Figure 1. Derating Curve Output Rectified Current




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Figure 3. Typical Forward Characteristics Per Diode




Figure 5. Typical Junction Capacitance Per Diode




Figure 4. Typical Reverse Leakage Characteristics Per Diode





Figure 6. Typical Transient Thermal Impedance

### PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.