


# Low Profile SMD 10Base-T Interface Module for PCMCIA EPE6050G




- Optimized for AMD/PHY type chip for Card Bus
- Robust construction allows for IR/VP processes
- Complies with or exceeds IEEE 802.3, 10Base-T Standards
- Isolation : 1500 (1 Minute)


### Electrical Parameters @ 25° C

Cut-Off Frequency (MHz)	Insertion Loss (dB Max.)	Return Loss (dB Min.)	Attenuation (dB Min.)				Common Mode Rejection (dB Min.)	Crosstalk (dB Min.)
			@ 20 MHz	@ 25 MHz	@ 30 MHz	@ 40 MHz		
± 1 MHz	1-10 MHz	5-10 MHz					30-100 MHz	1-10 MHz
Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Xmit/Rcv	Between Channels
17	-1/-1	-15/-15	-7/-7	-18/-18	-30/-30	-45/-45	-30/-30	-30

- **Isolation** : meets or exceeds 802.3 IEEE Requirements
- **Characteristic Filter Impedance** : 100 Ω
- Referenced to the filter output @ 5 MHz for filter only, excluding resistor network



**Note :** All resistors are ± 1%, unless otherwise specified



Unless Otherwise Specified Dimensions are in Inches /mm ± .010 /.25