



CHENMKO ENTERPRISE CO.,LTD

Lead free devices

SURFACE MOUNT

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE 20 - 60 Volts CURRENT 5.0 Amperes

SSM52PT

THRU

SSM56PT

FEATURES

- * Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- * For surface mounted applications
- * Low profile package
- * Built-in strain relief
- * Metal silicon junction, majority carrier conduction
- * Low power loss, high efficiency
- * High current capability, low forward voltage drop
- * High surge capability
- * For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- * High temperature soldering guaranteed : 260°C/10 seconds at terminals

MECHANICAL DATA

Case: JEDEC SMB molded plastic


Terminals: Solder plated, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Weight: 0.003 ounce 0.093 gram



SMA



SMA

MAXIMUM RATINGS (At Ta = 25°C unless otherwise noted)

RATINGS	SYMBOL	SSM52PT	SSM53PT	SSM54PT	SSM55PT	SSM56PT	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	20	30	40	50	60	Volts
Maximum RMS Voltage	VRMS	14	21	28	35	42	Volts
Maximum DC Blocking Voltage	Vdc	20	30	40	50	60	Volts
Maximum Average Forward Rectified Current	Io	5.0					Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	IFSM	125					Amps
Typical Junction Capacitance (Note 2)	Cj	300					pF
Typical Thermal Resistance (Note 1)	R θJL	12					°C / W
Operating and Storage Temperature Range	Tj, Tstg	-65 to +125					°C

ELECTRICAL CHARACTERISTICS (At Ta = 25°C unless otherwise noted)

CHARACTERISTICS		SYMBOL	SSM52PT	SSM53PT	SSM54PT	SSM55PT	SSM56PT	UNITS
Maximum Instantaneous Forward Voltage at 5.0 A DC		V _F	0.55			0.70		Volts
Maximum Average Reverse Current	@ T _A = 25°C	I _R	0.5					mAmps
at Rated DC Blocking Voltage	@ T _A = 100°C		20					mAmps

NOTES : 1. Thermal Resistance (Junction to Lead) : PC Board Mounted on 0.55 X 0.55" (14 X 14mm) copper pad area.
2. Measured at 1.0 MHz and applied reverse voltage of 4.0 volts.

2007-4

RATING CHARACTERISTIC CURVES (SSM52PT THRU SSM56PT)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - INSTANTANEOUS FORWARD CURRENT, (A)




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

