

NEW 200W Outdoor TWT Amplifier for Satellite Communications

The T02UO-2G

200 Watt TWT Power Amplifier — higher efficiency in an environmentally sealed compact package designed for outdoor operation

Ku-Band



note: photo is not necessarily representative of your desired configuration

Less Prime Power, More Efficient

CPI's new environmentally sealed 200 W Ku-band hubmount TWTA is the most efficient amplifier in its class. Consuming only 650 W prime power to achieve 175 W at the flange, the Mini-Ku is at least 24% more efficient than any similar product.

Reliable

Designed and built to survive in extremely adverse environmental conditions. Operates in ambient temperatures up to 60°C.

Digital Ready, Simple to Operate

User-friendly microprocessor-controlled logic. Integrated Ethernet computer interface and forward power detection over CIF are now standard. A variety of optional configurations, including integral linearizers and BUCs, is available.

Highly Compact

10% smaller and 25% lighter than any other 200 W TWTA.

Easy to Maintain

Modular design and built-in fault diagnostic capability via remote monitor and control.

Global Applications

Meets International Safety Standard EN-60215, Electromagnetic Compatibility 2004/108/EC and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements.

Worldwide Support

Backed by over three decades of satellite communications experience and CPI's worldwide 24-hour customer support network that includes sixteen regional factory service centers.

satcom  **division**

811 Hansen Way
P.O. Box 51625, Palo Alto, CA 94303

tel: +1 (650) 846-3803

fax: +1 (650) 424-1744

e-mail: satcommarketing@cpil.com
www.cpil.com/satcom

Ku-Band

200W Outdoor TWT Amplifier

OPTIONS:

- Remote Control Panel
- Redundant Subsystems
- Integrated 1:1 switch control and drive
- Integral Linearizer
- Extended Frequency --- 12.75 - 14.50 GHz
- Integral L-Band Block Upconverter (BUC --- option is available over 12.75 to 13.25 GHz OR 13.75 to 14.50 GHz frequency ranges only)
- Attenuated Solid State IPA

SPECIFICATIONS, T02UO-2G

Electrical

Frequency	13.75 to 14.50 GHz (output, wideband option 12.75 to 14.50 GHz) 950 MHz to 1700 MHz (input w/BUC option)
Output Power	
TWT	200 W min. (53.01 dBm)
Flange	175 W min. (52.43 dBm)
Bandwidth	750 MHz (1750 MHz with wideband option)
Gain	35 dB min. at rated power output (68 dB min. with SSIPA option); 41 dB min. at small signal (70 dB min. with SSIPA option)
Gain Stability	±0.45 dB/24hr max. (at constant drive and temp.)
Small Signal Gain Slope	±0.04 dB/MHz max.
Small Signal Gain Variation	1.0 dB pk-pk across any 80 MHz band; 3.5 dB pk-pk across the 750 MHz band 5.0 dB pk-pk across 1750 MHz (wideband option)
RF Level Adjust Range	30 dB typ. (not available with low gain version)
Input VSWR	1.3:1 max.
Output VSWR	2.2:1 max. (1.3:1 max. with optional output circulator)
Load VSWR	2.0:1 max. continuous operation; any value for operation without damage
MUXed External 10 MHz Reference Phase Noise	-120 dBc/Hz at 10 Hz
Required (L-Band Input 950 - 1700 MHz) ¹	-140 dBc/Hz at 100 Hz
	-145 dBc/Hz at 1 kHz
	-150 dBc/Hz at ≥10 kHz
BUC option only	(Level -3 to +7 dBm)
Single Sideband Phase Noise	-63 dBc at 100 Hz offset
BUC option only	-73 dBc at 1 kHz offset
	-83 dBc at 10 kHz offset
	-93 dBc at 100 kHz offset
	-103 dBc at 1 MHz offset
	-113 dBc at ≥10 MHz offset
Residual AM	-50 dBc below 10 kHz -20 [1.5 + log F(kHz)] dBc 10 kHz to 500 kHz
Phase Noise	12 dB below IESS-308 continuous mask (3 dB below mask with BUC option)
Spurious	-60 dBc max. at 175 W flange output
AM/PM Conversion	2.0°/dB max. for a single carrier up to 7 dB OBO (up to 4 dB OBO with linearizer option)
Harmonic Output	-60 dBc max. at rated power
Noise Power Density (at maximum gain)	<-130 dBW/4 kHz, below 12.7 GHz <-70 dBW/4 kHz, passband <-66 dBW/4 kHz, passband with linearizer

Electrical (continued)

Intermodulation	-24 dBc max. with respect to the sum of both carriers at total output power 7 dB OBO (4 dB OBO with optional linearizer)
Primary Power	100-240 VAC ±10% single phase, 47-63 Hz
Power Consumption	650 W typ.
Power Factor	0.95 min.

Environmental (Operating)

Ambient Temperature	-40°C to +60°C operating, including solar loading; -40°C to +71°C non-operating
Relative Humidity	100% condensing
Altitude	10,000 ft. with standard adiabatic derating of 2°C/1000 ft., operating; 50,000 ft., non-operating
Shock	20 g pk, 11 ms, 1/2 sine
Vibration	3 grms
Acoustic Noise	65 dBA @ 3 ft. from amplifier

Mechanical

Cooling	Forced air with integral blower
L-Band Input Connection	Type N female (BUC option only)
RF Input Connection	Type N female (standard)
RF Output Connection	WR-75 waveguide flange, grooved with UNC 2B 6-32 threaded holes
RF Output Monitor	Type N female, 44 dB nom.
Dimensions (W x H x D)	8.5 x 8.5 x 15.0 in. max. (216 x 216 x 381 mm)
Weight	24.25 lbs (11.0 kg) with no options; 25.41 lbs (11.5 kg) with BUC

Note 1: External 10 MHz reference must be multiplexed with the RF input signal.



Communications & Power Industries

satcom division

For more detailed information, please refer to the corresponding CPI Technical Description.

Note: Specifications may change without notice as a result of additional data or product refinement.

Please contact CPI before using this information for system design.