

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI HF20-12S** is Designed for 12.5 V Class AB & C HF Power Amplifier Applications in the 2 to 32 MHz Band.

FEATURES:

- $P_G = 15$ dB min. at 20 W/30 MHz
- $IMD_3 = -30$ dBc max. at 20 W(PEP)
- **Omnigold™** Metalization System
- Emitter Ballasting

MAXIMUM RATINGS

I_C	4.5 A
V_{CBO}	36 V
V_{CEO}	18 V
V_{EBO}	4.0 V
P_{DISS}	80 W @ $T_C = 25$ °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	2.2 °C/W

PACKAGE STYLE .380 4L STUD

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.980 / 24.89	
C	.370 / 9.40	.385 / 9.78
D	.004 / 0.10	.007 / 0.18
E	.320 / 8.13	.330 / 8.38
F	.100 / 2.54	.130 / 3.30
G	.450 / 11.43	.490 / 12.45
H	.090 / 2.29	.100 / 2.54
I	.155 / 3.94	.175 / 4.45
J		.750 / 19.05

ORDER CODE: ASI10595

CHARACTERISTICS $T_C = 25$ °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 50$ mA	36			V
BV_{CES}	$I_C = 50$ mA	36			V
BV_{CEO}	$I_C = 50$ mA	18			V
BV_{EBO}	$I_E = 5.0$ mA	4.0			V
I_{CES}	$V_{CE} = 15$ V			5	mA
h_{FE}	$V_{CE} = 5.0$ V $I_C = 1.0$ A	10		200	---
C_{ob}	$V_{CB} = 12.5$ V $f = 1.0$ MHz		100		pF
G_P IMD_3	$V_{CC} = 12.5$ V $I_{CQ} = 25$ mA $f = 30$ MHz $P_{OUT} = 20$ W (PEP)	15		-30	dB dBc