

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0940303910](#)  
**Status:** **Active**  
**Description:** Quick Disconnect, Female, for 1.00-2.50mm<sup>2</sup> (14-16 AWG) wire, Accepts 6.35mm (.250") x 0.81mm (.032") Tab

**Documents:**

[Drawing \(PDF\)](#) [Product Specification PS-94030-002 \(PDF\)](#)  
[Product Specification PS-94030-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

Product Family	Quick Disconnects
Series	<a href="#">94030</a>
Crimp Quality Equipment	Yes
Product Name	N/A
Type	Quick Disconnect

**Physical**

Barrel Type	Open
Gender	Female
Glow-Wire Compliant	No
Insulation	None
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Unplated
Orientation	Straight
Packaging Type	Reel
Polarized to Mating Part	Yes
Tab Thickness	0.81mm (.032")
Tab Width	6.35mm (.250")
Temperature Range - Operating	80°C
Wire Insulation Diameter	2.70-4.30mm (.106-.169")
Wire Size AWG	14, 16
Wire Size mm <sup>2</sup>	1.00-2.50


**Electrical**

Voltage - Maximum	250V
-------------------	------

**Material Info**

**Reference - Drawing Numbers**

Product Specification	PS-94030-001, PS-94030-002
Sales Drawing	94030-391X-SD



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC Contains SVHC: No**  
**Halogen-Free Status**  
**Halogen-Free**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[94030Series](#)

**Use With**

[94090-4080](#) , [94090-4100](#) , [94090-4120](#) ,  
[94090-4140](#) , [94090-4150](#) , [94090-4170](#) ,  
[94090-4180](#) , [94090-4200](#) , [94503-0200](#) ,  
[94503-0210](#) , [94503-0800](#)

