

SPECIFICATIONS			
PARAMETERS	VALUES	UNITS	
RATED INPUT POWER	2	W	
MAX INPUT POWER	4	W	
IMPEDANCE	4 ± 15%	ОНМ	
OUTPUT SPL @ 1W/0.5M	87 ± 3	dBA	
(AT 0.8, 1.0, 1.2, 1.5, kHz)	6/ ± 3		
DISTORTION (MAX.)	5%	-	
RESONANT FREQUENCY	370 ± 20%	Hz	
FREQUENCY RANGE	200 ~ 20,000	Hz	
HOUSING MATERIAL	ABS	-	
CONE MATERIAL	PAPER	-	
MAGNET MATERIAL	Nd-Fe-B	-	
OPERATING TEMPERATURE	-40 ~ +85 °C		
WEIGHT	16.5	grams	

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

	REVISION HISTORY			
LTR	DESCRIPTION	DATE	APPROVED	
-	- RELEASED FROM ENGINEERING 12/7/2005			
Α	ADDED MOUNTING HOLE DIMENSION	12/18/2007	R.W.	
В	REVISED MAX. INPUT POWER	7/18/2008	B.R.	
C	REVISED OPERATING TEMPERATURE	10/14/2008	C.W.	
D	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	11/8/2008	B.R.	





Designed by



- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED:	CLZE	
DIMENSIONS ARE IN MILLIMETERS.	SIZE	
TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.		
AS04004F	O-R.idw	

J.A.F.	12/6/2005	Е	3.R.
00	n III		
W Y	Įβui,		
)audio	\mathbf{C}	
700	A Division of Projects Unlin	mited	

Checked by

AS04004PO-R					
	12/7/2005	E.P.	12/7/2005	11/8/2008	
	Date	Approved by	Date	Diawii Date	

Speaker Edition Sheet