


### Power MOSFET

| PRODUCT SUMMARY            |                       |
|----------------------------|-----------------------|
| $V_{DS}$ (V) at $T_J$ max. | 560 V                 |
| $R_{DS(on)}$ ( $\Omega$ )  | $V_{GS} = 10$ V 0.555 |
| $Q_g$ (Max.) (nC)          | 48                    |
| $Q_{gs}$ (nC)              | 12                    |
| $Q_{gd}$ (nC)              | 15                    |
| Configuration              | Single                |

### FEATURES

- Low Figure-of-Merit  $R_{on} \times Q_g$
- 100 % Avalanche Tested
- Gate Charge Improved
- $T_{rr}/Q_{rr}$  Improved
- Compliant to RoHS Directive 2002/95/EC



| ORDERING INFORMATION |               |                |                |
|----------------------|---------------|----------------|----------------|
| Package              | TO-220AB      | D2PAK (TO-263) | TO-220 FULLPAK |
| Lead (Pb)-free       | SiHP12N50C-E3 | SiHB12N50C-E3  | SiHF12N50C-E3  |

| PARAMETER   | SYMBOL         | LIMIT                      |                   | UNIT |   |
|---|----------------|----------------------------|-------------------|------|---|
|   |                | TO220-AB<br>D2PAK (TO-263) | TO-220<br>FULLPAK |      |   |
| Drain-Source Voltage                                      | $V_{DS}$       | 500                        |                   | V    |   |
| Gate-Source Voltage                                       | $V_{GS}$       | $\pm 30$                   |                   |      |   |
| Continuous Drain Current ( $T_J = 150$ °C) <sup>a</sup>   | $I_D$          | 12                         |                   |      | A |
|   |                | 7.5                        |                   |      |   |
| Pulsed Drain Current <sup>c</sup>                         | $I_{DM}$       | 28                         |                   |      |   |
| Linear Derating Factor                                    |                | 1.67                       | 0.28              | W/°C |   |
| Single Pulse Avalanche Energy <sup>b</sup>                | $E_{AS}$       | 180                        |                   | mJ   |   |
| Maximum Power Dissipation                                 | $P_D$          | 208                        | 36                | W    |   |
| Operating Junction and Storage Temperature Range          | $T_J, T_{stg}$ | - 55 to + 150              |                   | °C   |   |
| Soldering Recommendations (Peak Temperature) <sup>d</sup> | for 10 s       | 300                        |                   |      |   |

#### Notes

- Limited by maximum junction temperature.
- $V_{DD} = 50$  V, starting  $T_J = 25$  °C,  $L = 2.5$  mH,  $R_g = 25$  Ω,  $I_{AS} = 12$  A.
- Repetitive rating; pulse width limited by maximum junction temperature.
- 1.6 mm from case.

\* Pb containing terminations are not RoHS compliant, exemptions may apply

**THERMAL RESISTANCE RATINGS**

| PARAMETER                                    | SYMBOL            | TO220-AB D <sup>2</sup> PAK (TO-263) | TO-220 FULLPAK | UNIT |
|--|-------------------|--------------------------------------|----------------|------|
| Maximum Junction-to-Ambient                  | R <sub>thJA</sub> | 62                                   | 65             | °C/W |
| Maximum Junction-to-Case (Drain)             | R <sub>thJC</sub> | 0.6                                  | 3.5            |      |
| Junction-to-Ambient (PCB mount) <sup>a</sup> | R <sub>thJA</sub> | 40                                   | -              |      |

**Note**





- a. When mounted on 1" square PCB (FR-4 or G-10 material).

**SPECIFICATIONS (T<sub>J</sub> = 25 °C, unless otherwise noted)**

| PARAMETER                                      | SYMBOL                           | TEST CONDITIONS  |  | MIN. | TYP. | MAX.  | UNIT |
|--|----------------------------------|--|--|------|------|-------|------|
| <b>Static</b>                                  |                                  |  |  |      |      |       |      |
| Drain-Source Breakdown Voltage                 | V <sub>DS</sub>                  | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA   |  | 500  | -    | -     | V    |
| V <sub>DS</sub> Temperature Coefficient        | ΔV <sub>DS</sub> /T <sub>J</sub> | Reference to 25 °C, I <sub>D</sub> = 1 mA  |  | -    | 0.6  | -     | V/°C |
| Gate-Source Threshold Voltage (N)              | V <sub>GS(th)</sub>              | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA  |  | 3.0  | -    | 5.0   | V    |
| Gate-Source Leakage                            | I <sub>GSS</sub>                 | V <sub>GS</sub> = ± 30 V   |  | -    | -    | ± 100 | nA   |
| Zero Gate Voltage Drain Current                | I <sub>DSS</sub>                 | V <sub>DS</sub> = 500 V, V <sub>GS</sub> = 0 V   |  | -    | -    | 50    | μA   |
|  |                                  | V <sub>DS</sub> = 400 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125 °C                              |  | -    | -    | 250   |      |
| Drain-Source On-State Resistance               | R <sub>DS(on)</sub>              | V <sub>GS</sub> = 10 V   | I <sub>D</sub> = 4 A                           | -    | 0.46 | 0.555 | Ω    |
| Forward Transconductance                       | g <sub>f</sub>                   | V <sub>DS</sub> = 50 V, I <sub>D</sub> = 3 A   |  | -    | 3    | -     | S    |
| <b>Dynamic</b>                                 |                                  |  |  |      |      |       |      |
| Input Capacitance                              | C <sub>iss</sub>                 | V <sub>GS</sub> = 0 V,<br>V <sub>DS</sub> = 25 V,<br>f = 1.0 MHz                                     |  | -    | 1375 | -     | pF   |
| Output Capacitance                             | C <sub>oss</sub>                 |  |  | -    | 165  | -     |      |
| Reverse Transfer Capacitance                   | C <sub>rss</sub>                 |  |  | -    | 17   | -     |      |
| Total Gate Charge                              | Q <sub>g</sub>                   | V <sub>GS</sub> = 10 V   | I <sub>D</sub> = 10 A, V <sub>DS</sub> = 400 V | -    | 32   | 48    | nC   |
| Gate-Source Charge                             | Q <sub>gs</sub>                  |  |  | -    | 12   | -     |      |
| Gate-Drain Charge                              | Q <sub>gd</sub>                  |  |  | -    | 15   | -     |      |
| Turn-On Delay Time                             | t <sub>d(on)</sub>               | V <sub>DD</sub> = 250 V, I <sub>D</sub> = 10 A<br>R <sub>g</sub> = 4.3 Ω, V <sub>GS</sub> = 10 V     |  | -    | 18   | -     | ns   |
| Rise Time                                      | t <sub>r</sub>                   |  | -  | 35   | -    |       |      |
| Turn-Off Delay Time                            | t <sub>d(off)</sub>              |  | -  | 23   | -    |       |      |
| Fall Time                                      | t <sub>f</sub>                   |  | -  | 6    | -    |       |      |
| Gate Input Resistance                          | R <sub>g</sub>                   | f = 1 MHz, open drain  |  | -    | 1.1  | -     | Ω    |
| <b>Drain-Source Body Diode Characteristics</b> |                                  |  |  |      |      |       |      |
| Continuous Source-Drain Diode Current          | I <sub>S</sub>                   | MOSFET symbol showing the integral reverse p - n junction diode                                      |  | -    | -    | 12    | A    |
| Pulsed Diode Forward Current                   | I <sub>SM</sub>                  |  |  | -    | -    | 28    |      |
| Body Diode Voltage                             | V <sub>SD</sub>                  | T <sub>J</sub> = 25 °C, I <sub>S</sub> = 10 A, V <sub>GS</sub> = 0 V                                 |  | -    | -    | 1.8   | V    |
| Body Diode Reverse Recovery Time               | t <sub>rr</sub>                  | T <sub>J</sub> = 25 °C, I <sub>F</sub> = I <sub>S</sub> , dI/dt = 100 A/μs,<br>V <sub>R</sub> = 20 V |  | -    | 580  | -     | ns   |
| Body Diode Reverse Recovery Charge             | Q <sub>rr</sub>                  |  | -  | 4.3  | -    |       |      |
| Body Diode Reverse Recovery Current            | I <sub>RRM</sub>                 |  | -  | 13   | -    | A     |      |

**Note**

- The information shown here is a preliminary product proposal, not a commercial product data sheet. Vishay Siliconix is not committed to produce this or any similar product. This information should not be used for design purposes, nor construed as an offer to furnish or sell such products.

**TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)

**Fig. 1 - Typical Output Characteristics (TO-220)**

**Fig. 3 - Typical Transfer Characteristics**

**Fig. 2 - Typical Output Characteristics (TO-220)**

**Fig. 4 - Normalized On-Resistance vs. Temperature**




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage




Fig. 8 - Maximum Safe Operating Area (TO-220AB, D<sup>2</sup>PAK)




Fig. 9 - Maximum Safe Operating Area (TO-220 FULLPAK)




Fig. 10a - Switching Time Test Circuit




Fig. 10b - Switching Time Waveforms




Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case (TO-220AB, D<sup>2</sup>PAK)




Fig. 12 - Maximum Effective Transient Thermal Impedance, Junction-to-Case (TO-220 FULLPAK)




Fig. 13a - Unclamped Inductive Test Circuit




Fig. 13b - Unclamped Inductive Waveforms




Fig. 14a - Basic Gate Charge Waveform





Fig. 14b - Gate Charge Test Circuit



**Fig. 15 - For N-Channel**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?91388](http://www.vishay.com/ppg?91388).



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.