



PNP BD684 TO3 (Temporary part number)

## SILICON DARLINGTON POWER TRANSISTORS

PNP epitaxial-base transistors in monolithic Darlington circuit for audio and video applications.

They are mounted in Jedec TO-3 metal package.

Compliance to RoHS.

### ABSOLUTE MAXIMUM RATINGS

| Symbol     | Ratings                   | Value                         | Unit             |
|------------|---------------------------|-------------------------------|------------------|
| $-V_{CEO}$ | Collector-Emitter Voltage | 140                           | V                |
| $-V_{CBO}$ | Collector-Base Voltage    | 140                           | V                |
| $-V_{EBO}$ | Emitter-Base Voltage      | 5                             | V                |
| $-I_C$     | Collector Current         | $-I_C$                        | A                |
|            |                           | $-I_{CM}$                     |                  |
| $-I_B$     | Base current (peak value) | $-I_{BM}$                     | A                |
| $P_T$      | Total power Dissipation   | @ $T_{mb} = 25^\circ\text{C}$ | Watts            |
| $T_J$      | Junction Temperature      | 150                           | $^\circ\text{C}$ |
| $T_{Stg}$  | Storage Temperature       | -65 to +150                   | $^\circ\text{C}$ |

### THERMAL CHARACTERISTICS

| Symbol       | Ratings                                             | Value | Unit |
|--------------|-----------------------------------------------------|-------|------|
| $R_{thJ-mb}$ | Thermal Resistance, Junction to mounting base       | 3.12  | K/W  |
| $R_{thJ-a}$  | Thermal Resistance, Junction to ambient in free air | 100   | K/W  |

## PNP BD684 TO3 (Temporary part number)

### ELECTRICAL CHARACTERISTICS


TC=25°C unless otherwise noted

| Symbol         | Ratings                              | Test Condition(s)                                                                                                            | Min           | Typ              | Mx          | Unit          |
|----------------|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------|---------------|------------------|-------------|---------------|
| $-I_{CBO}$     | Collector cut-off current            | $I_E=0, -V_{CB}=-V_{CEOMAX}=140\text{ V}$<br>$I_E=0, -V_{CB}=-1/2V_{CBOMAX}=70\text{ V}, T_J=150^\circ\text{C}$              | -             | -                | 0,2<br>1    | mA            |
| $-I_{CEO}$     | Collector cut-off current            | $I_B=0, -V_{CE}=-1/2V_{CEOMAX}=70\text{ V}$                                                                                  | -             | -                | 0,2         | mA            |
| $-I_{EBO}$     | Emitter cut-off current              | $I_C=0, -V_{EB}=5\text{ V}$                                                                                                  | -             | -                | 5           | mA            |
| $-V_{CE(SAT)}$ | Collector-Emitter saturation Voltage | $-I_C=1.5\text{ A}, -I_B=6\text{ Ma}$                                                                                        | -             | -                | 2           | V             |
| $h_{FE}$       | DC Current Gain                      | $-V_{CE}=3\text{ V}, -I_C=500\text{ mA}$<br>$-V_{CE}=3\text{ V}, -I_C=1,5\text{ A}$<br>$-V_{CE}=3\text{ V}, -I_C=4\text{ A}$ | -<br>750<br>- | 2000<br>-<br>750 | -<br>-<br>- |               |
| $-V_{BE}$      | Base-Emitter Voltage(1&2)            | $-V_{CE}=3\text{ V}, -I_C=1,5\text{ A}$                                                                                      | -             | -                | 2,5         | V             |
| $h_{fe}$       | Small signal current gain            | $-V_{CE}=3\text{ V}, -I_C=1,5\text{ A}, f=1\text{ MHz}$                                                                      | 10            | -                | -           |               |
| $f_{hfe}$      | Ut-off frequency                     | $-V_{CE}=3\text{ V}, -I_C=1,5\text{ A}$                                                                                      | -             | 60               | -           | kHz           |
| $V_F$          | Diode forward voltage                | $I_F=1,5\text{ A}$                                                                                                           | -             | 1,5              | -           | V             |
| $-I_{(SB)}$    | Second-breakdown collector current   | $-V_{CE}=50\text{ V}, t_p=20\text{ms}, \text{non rep.}, \text{without heatsink (BD676 ; } V_{CE}=40\text{ V)}$               | 0,8           | -                | -           | A             |
| $t_{on}$       | Turn-on time                         | $-I_{con}=1,5\text{A}, I_{bon}=-I_{boff}=6\text{mA}, V_{CC}=30\text{V}$                                                      | -             | 0,8              | 2           | $\mu\text{s}$ |
| $t_{off}$      | Turn-off time                        |                                                                                                                              | -             | 4,5              | 8           |               |

1. Measured under pulse conditions :  $t_p < 300\mu\text{s}$ ,  $\delta < 2\%$ .
2.  $V_{BE}$  decreases by about 3,6 mV/K with increasing temperature.

### MECHANICAL DATA CASE TO-3

| DIMENSIONS |       |        |
|------------|-------|--------|
|            | mm    | inches |
| A          | 25,51 | 1,004  |
| B          | 38,93 | 1,53   |
| C          | 30,12 | 1,18   |
| D          | 17,25 | 0,68   |
| E          | 10,89 | 0,43   |
| G          | 11,62 | 0,46   |
| H          | 8,54  | 0,34   |
| L          | 1,55  | 0,6    |
| M          | 19,47 | 0,77   |
| N          | 1     | 0,04   |
| P          | 4,06  | 0,16   |



|         |           |
|---------|-----------|
| Pin 1 : | Base      |
| Pin 2 : | Emitter   |
| Case :  | Collector |