

3A Series

3W DC-DC Converters

Features

- 3W Isolated Output
- 24-Pin DIP Package
- Efficiency to 80%
- 2:1 Input Range
- Regulated Outputs
- Pi Input Filter
- Continuous Short Circuit Protection

Model Number	Input Voltage	Output Voltage	Output Current	Input Current		% Efficiency	Case
				No Load	Full Load		
3A-01	4.5-6.0VDC	5 VDC	600 mA	15 mA	850 mA	70	A
3A-02		12 VDC	250 mA	15 mA	800 mA	75	
3A-03		15 VDC	200 mA	15 mA	800 mA	75	
3A-04		±5 VDC	±300 mA	25 mA	850 mA	70	
3A-05		±12 VDC	±125 mA	25 mA	800 mA	75	
3A-06		±15 VDC	±100 mA	25 mA	800 mA	75	
3A-07		3.3 VDC	600 mA	15 mA	650 mA	61	
3A-11	9-18VDC	5 VDC	600 mA	7.5 mA	340 mA	73	A
3A-12		12 VDC	250 mA	7.5 mA	320 mA	78	
3A-13		15 VDC	200 mA	7.5 mA	320 mA	78	
3A-14		±5 VDC	±300 mA	12 mA	340 mA	73	
3A-15		±12 VDC	±125 mA	12 mA	320 mA	78	
3A-16		±15 VDC	±100 mA	12 mA	320 mA	78	
3A-17		3.3 VDC	600mA	7.5 mA	254 mA	65	
3A-21	18-36VDC	5 VDC	600 mA	5 mA	168 mA	74	A
3A-22		12 VDC	250 mA	5 mA	156 mA	80	
3A-23		15 VDC	200 mA	5 mA	156 mA	80	
3A-24		±5 VDC	±300 mA	7.5 mA	168 mA	74	
3A-25		±12 VDC	±125 mA	7.5 mA	156 mA	80	
3A-26		±15 VDC	±100 mA	7.5 mA	156 mA	80	
3A-27		3.3 VDC	600 mA	5 mA	125 mA	66	
3A-31	36-72VDC	5 VDC	600 mA	2 mA	82 mA	76	A
3A-32		12 VDC	250 mA	2 mA	78 mA	80	
3A-33		15 VDC	200 mA	2 mA	78 mA	80	
3A-34		±5 VDC	±300 mA	3 mA	82 mA	76	
3A-35		±12 VDC	±125 mA	3mA	80 mA	78	
3A-36		±15 VDC	±100 mA	3 mA	80 mA	78	
3A-37		3.3 VDC	600 mA	3 mA	61 mA	68	

