



## Features


- Thin film construction
- Hermetic package TO-8B
- Operating temperature range: -55°C ~ +85°C

**Specifications** (measured in a 50 Ω system, V<sub>cc</sub>=+15V, T<sub>A</sub>=-55°C ~ +85°C)

Parameter	Symbol	Unit	Guaranteed	Typical
Frequency Range	f <sub>L</sub> ~ f <sub>H</sub>	MHz	20 ~ 1000	—
Attenuation(Max)	A <sub>Max</sub>	dB	24	26
Insertion loss	IL	dB	2.0	1.5
VSWR of input/output	VSWR	—	2.0 : 1	1.5 : 1
DC Supply	V <sub>cc</sub>	V	—	+15
DC Current	I <sub>cc</sub>	mA	—	14
Control voltage	V <sub>co</sub>	V	—	0 ~ 15
Control Current	I <sub>co</sub>	mA	—	0 ~ 7

## Absolute Maximum Ratings


DC Supply: +18VDC  
Input Power: +20dBm  
Storage Temp: +125°C



TO- 8B

## Application Notes

1. Functional schematic shown as following, which include an internal coupling capacitor.
2. Interexchangeable input and output ports
3. Cascaded with amplifier can be used as VGC amplifier
4. See assembly section for mounting method



1. V<sub>cc</sub>      4. RF output  
2. RF input    5. V<sub>co</sub>  
3. GND

## Typical Performance

