

PBN7C Series

74-294 WATTS THREE STEP CHARGER

Features

- 3-step charge control with timer.
Charge current not affected by fluctuations in mains voltage.
- Medical approved – EN 60601 (74W & 147W model).
- Protected against reversed polarity and short circuit proof.
- LED-indicator with three different colours
- Waterproof (IP67) version available (147W & 294W model).
- CE-marked, C-Tick.



Specifications

INPUT

Input voltage	190-264Vac (74W & 147W model). 198-264Vac (294W model).
---------------	--

Input Frequency	47-63 Hz
-----------------	----------

OUTPUT

Output Voltage	14.7V cycle, -13.7V standby 29.4V cycle – 27.4V standby
----------------	--

Charge Current	See table
----------------	-----------

Ripple	<100mV p-p
--------	------------

Current Limit	Yes
---------------	-----

OPERATING

Efficiency	Greater than 83%
------------	------------------

Switch Frequency	63kHz
------------------	-------

Leakage Current with Mains	
----------------------------	--

Disconnected	<2.5mA (12V battery voltage)
--------------	------------------------------

Insulation Class	1
------------------	---

Insulation Voltage	Primary – ground 1250Vac (74W & 147W model). 1500Vac (300W model). Primary – secondary 3750Vac (74W & 147W model). 4000Vac (294W model). Secondary – ground 500VAC
--------------------	---

Indication	Orange – Boost, constant current. Red - Boost, constant current (294W model). Yellow – Timer, constant voltage. Green – Float, constant voltage.
------------	---

Timer	2h 30min (74W & 147W model). 4h 30min (294W model).
-------	--

ENVIRONMENTAL

Temperature range	-25°C - +40°C
-------------------	---------------

STANDARDS AND APPROVALS

Electrical Safety Standard	EN60335-2-29. EN 60601-1 (74W & 147W model).
----------------------------	---

EMC Standards	
Medical	EN 60601-1-2 (74W & 147W model).
Emission	EN 61000-6-3
Immunity	EN 61000-6-1

C-Tick	AS/NZS2064 CISPR11: Group 1, Class A
--------	--------------------------------------

MECHANICAL

IP grade	IP 20 (PCB/components Protected with coating)
----------	---

Dimensions (LxWxH)	PBN7C-L: 158 x 171 x 54mm. PBN7C-R: 184 x 171 x 54mm. PBN7C-T: 215 x 186 x 63.5mm.
--------------------	--

Weight	PBN7C-L: 1.27kg. PBN7C-R: 1.5KG. PBN7C-T: 4KG.
--------	--

Selection Table

MODEL NUMBER	TIMER MODE (VDC)	STANDBY MODE (VDC)	CHARGE CURRENT (A)	MAX POWER (W)
PBN7C-12L	14.7	13.7	5	74
PBN7C-12R	14.7	13.7	10	147
PBN7C-12T	14.7	13.7	20	294
PBN7C-24L	29.4	27.4	2.5	74
PBN7C-24R	29.4	27.4	5	147
PBN7C-24T	29.4	27.4	10	294
PBN7C-36R	44.1	40.8	3.3	147
PBN7C-36T	44.1	40.8	6.7	294
PBN7C-48R	58.8	54.8	2.5	147
PBN7C-48T	58.8	54.8	5	294