



Features

- ◆ 19" 2U high, rackmount chassis compliant to EIA RS-310C standard
- ◆ Detachable card cage for easy installation and maintenance
- ◆ Provides mainboard, 250W ATX power supply (PCI x 3 or PCI x 2 + AGP x 1)
- ◆ External: 5.25" space x 1 + 3.5" space x 1
- ◆ Internal: 3.5" space x 3
- ◆ Dual lockable latch doors
- ◆ FCC/CE industrial Class A approval
- ◆ 8cm ball bearing cooling fan x 3 (optional)
- ◆ System environmental monitor (optional)

Specifications

Chassis

Meets EIA RS-310C 19" 2U high, rackmount standard; heavy-duty steel, SECC 1.2t (Japan)

Drive Space

External: 5.25" space x 1 + 3.5" space x 1
Internal: 3.5" space x 3

Front Panel

Power switch, reset button; power and HDD active LED

Thermal Solution

8cm ball bearing cooling fan x 3 (optional); system environmental monitor (optional) and removable air filter

Altitude

15,000 feet

Power Supply

250W ATX power supply

Temperature

0~+50°C (operating); 0~+70°C (storage)

Humidity

5~95%; non-condensing

Safety Standard

FCC/CE on chassis and FCC/CE/UL/TUV on power supply

Dimensions (L x W x H)

48.0 x 42.7 x 8.82 cm

Ordering Guide

- ◆ **RC-720B**
19" 2U High, Full-size Rackmount Chassis
- ◆ **RC-720BA**
RC-720B Chassis w/250W ATX P/S