


Anode Gate Silicon Controlled Rectifier Series 050R



Note 1: 1/4-28 UNF-3A

Note 2: Full thread within 2 1/2 threads

Dim.	Inches		Millimeter		
	Minimum	Maximum	Minimum	Maximum	Notes
A	---	---	---	---	1
B	.677	.685	17.20	17.40	
C	---	.770	---	19.56	
D	1.200	1.250	30.48	31.75	
E	.427	.447	10.84	11.35	
F	.115	.155	2.92	3.94	
G	---	.515	---	13.08	
H	.220	.249	5.58	6.32	2
J	.200	.300	5.08	7.62	
K	.120	---	3.05	---	
M	---	.667	---	16.94	Dia.
N	.065	.085	1.65	2.15	
P	.145	.155	3.68	3.93	Dia.
R	.055	.065	1.40	1.65	Dia.
S	.025	.030	.64	.76	

TO-208AC (TO-65)

Microsemi Catalog Number

050R02GOF
050R04GOF
050R06GOF
050R08GOF
050R10GOF
050R12GOF

Forward & Reverse Repetitive Blocking VDRM, VRMM

200
400
600
800
1000
1200

- dv/dt-200 V/usec
- 1200 Amperes surge current
- Economical for medium power applications
- Compact TO-208AC package

To specify dv/dt other than 200V/usec., contact factory.

Electrical Characteristics

Max. RMS on-state current
Max. average on-state cur.
Max. peak on-state voltage
Max. holding current
Max. peak one cycle
surge current
Max. I^2t capability for fusing

$|T_{(RMS)}$ 80 Amps
 $|T_{(AV)}$ 50 Amps
 V_{TM} 1.5 Volts
 $|H$ 200 mA
 $|T_{SM}$ 1200 Amps

I^2t 6000A²S

$T_C = 94^\circ C$
 $T_C = 94^\circ C$
 $|T_M = 200 A(\text{peak})$
 $T_C = 94^\circ C \text{ 60Hz}$
 $t = 8.3 \text{ ms}$

Thermal and Mechanical Characteristics

Operating junction temp range
Storage temperature range
Maximum thermal resistance
Typical thermal resistance (greased)
Mounting torque
Weight

T_J
 T_{STG}
 $R_{\theta JC}$
 $R_{\theta CS}$

-65°C to 125°C
-65°C to 150°C
0.35°C/W Junction to case
0.20°C/W Case to sink
25-30 inch pounds
0.56 ounces (16 grams) typical

3-31-03 Rev. 2



800 Hoyt Street
Broomfield, CO 80020
PH: (303) 469-2161
FAX: (303) 466-3775
www.microsemi.com

050R

$T_J = 25^\circ\text{C}$ unless otherwise indicated

Switching

Critical rate of rise of on-state current (note 1)	di/dt	200A/usec.	$T_J = 125^\circ\text{C}$
Typical delay time (note 1)	t_d	3.0 usec.	
Typical circuit commuted turn-off time (note 2)	t_q	100 usec.	$T_J = 125^\circ\text{C}$

Note 1: $I_{TM} = 50\text{A}$, $V_D = V_{DRM}$. $GT = 12\text{V}$ open circuit, 20Ω -0.1 usec. rise time
Note 2: $I_{TM} = 50\text{A}$, $di/dt = 5\text{A}/\mu\text{s}$, V_R during turn-off interval = 50V min.,
reapplied $dv/dt = 20\text{V}/\mu\text{s}$, linear to rated V_{DRM} , $V_{GT} = 0\text{V}$

Triggering - Third Quadrant

Max. gate voltage to trigger	V_{GT}	-3.0V	
Max. nontriggering gate voltage	V_{GD}	-0.25V	$T_J = 125^\circ\text{C}$
Max. gate current to trigger	I_{GT}	-100mA	
Max. peak gate power	PGM	10W	
Average gate power	$PG(AV)$	1.0W	$t_p = 10 \mu\text{s}$

NOTE: Triggering in the third quadrant requires a series gate current limiting resistor for 200mA and diode protection.

Blocking

Max. leakage current	I_{DRM}	6mA	$T_J = 125^\circ\text{C} \& V_{DRM}$
Max. reverse leakage	I_{RRM}	6mA	$T_J = 125^\circ\text{C} \& V_{RRM}$
Critical rate of rise of off-state voltage	dv/dt	200V/usec.	$T_J = 125^\circ\text{C}$

050R

Figure 1
Typical Forward On-State Characteristics




Figure 2
Forward Current Derating




Figure 3
Maximum Power Dissipation




Figure 4
Transient Thermal Impedance




Figure 5
Maximum Nonrepetitive Surge Current

