

## SKiiP 1202 GB 061 - 360 CTV

Absolute Maximum Ratings		Values	Units
Symbol	Conditions <sup>1)</sup>		
V <sub>isol</sub> <sup>4)</sup>	AC, 1min	2500	V
T <sub>op</sub> , T <sub>stg</sub>	Operating / stor. temperature	-25...+85	°C
IGBT and Inverse Diode			
V <sub>CES</sub>		600	V
V <sub>CC</sub> <sup>5)</sup>	Operating DC link voltage	400	V
I <sub>C</sub>	IGBT	1200	A
T <sub>j</sub> <sup>3)</sup>	IGBT + Diode	-40...+150	°C
I <sub>F</sub>	Diode	1200	A
I <sub>FM</sub>	Diode, t <sub>p</sub> < 1 ms	2400	A
I <sub>FSM</sub>	Diode, T <sub>j</sub> = 150 °C, 10ms; sin	12000	A
I <sup>2</sup> t (Diode)	Diode, T <sub>j</sub> = 150 °C, 10ms	720	kAs <sup>2</sup>
Driver			
V <sub>S1</sub>	Stabilized Power Supply	18	V
V <sub>S2</sub>	Non-stabilized Power Supply	30	V
f <sub>smax</sub>	Switching frequency	20	kHz
dV/dt	Primary to secondary side	75	kV/μs

Characteristics		min.	typ.	max.	Units
Symbol	Conditions <sup>1)</sup>				
IGBT <sup>11)</sup>					
V <sub>(BR)CES</sub>	Driver without supply	≥V <sub>CES</sub>	–	–	V
I <sub>CES</sub>	V <sub>GE</sub> = 0, T <sub>j</sub> = 25 °C	–	–	1,2	mA
	V <sub>CE</sub> = V <sub>CES</sub> T <sub>j</sub> = 125 °C	–	18	–	mA
V <sub>TO</sub>	T <sub>j</sub> = 125 °C	–	–	0,94	V
r <sub>T</sub>	T <sub>j</sub> = 125 °C	–	–	1,4	mΩ
V <sub>Cesat</sub>	I <sub>C</sub> = 1200A, T <sub>j</sub> = 125 °C	–	–	2,6	V
V <sub>Cesat</sub>	I <sub>C</sub> = 1200A, T <sub>j</sub> = 25 °C	–	–	2,60	V
E <sub>on</sub> + E <sub>off</sub>	V <sub>CC</sub> =300/400V, I <sub>C</sub> =1200A	–	–	108/153	mJ
	T <sub>j</sub> = 125 °C				
C <sub>CHC</sub>	per SKiiP, AC side	–	2,4	–	nF
L <sub>CE</sub>	Top, Bottom	–	5	–	nH
Inverse Diode <sup>2)</sup>					
V <sub>F</sub> = V <sub>EC</sub>	I <sub>F</sub> = 1200A; T <sub>j</sub> = 125 °C	–	–	1,72	V
V <sub>F</sub> = V <sub>EC</sub>	I <sub>F</sub> = 1200A T <sub>j</sub> = 25 °C	–	–	1,75	V
E <sub>on</sub> + E <sub>off</sub>	I <sub>F</sub> = 1200A; T <sub>j</sub> = 125 °C	–	–	36	mJ
V <sub>TO</sub>	T <sub>j</sub> = 125 °C	–	–	0,78	V
r <sub>T</sub>	T <sub>j</sub> = 125 °C	–	–	0,8	mΩ
Thermal Characteristics					
R <sub>thjs</sub> <sup>10)</sup>	per IGBT	–	–	0,033	K/W
R <sub>thjs</sub> <sup>10)</sup>	per Diode	–	–	0,063	K/W
R <sub>thsa</sub> <sup>6,10)</sup>	P16 heatsink; see case S3	–	–	36	K/KW
Driver					
I <sub>S1</sub>	Supply current 15V-supply	260+470*f <sub>s</sub> /f <sub>smax</sub> +1,3*I <sub>AC</sub> /A			mA
I <sub>S2</sub>	Supply current 24V-supply	200+320*f <sub>s</sub> /f <sub>smax</sub> +1,0*I <sub>AC</sub> /A			mA
t <sub>interlock-driver</sub>	Interlock-time	2,3			μs
SKiiPPACK protection					
I <sub>TRIPSC</sub>	Short circuit protection	1239			A
I <sub>TRIPLG</sub>	Ground fault protection				A
T <sub>TRIP</sub>	Over-temp. protection	115			°C
U <sub>DCTRIP</sub> <sup>9)</sup>	U <sub>DC</sub> -protection	410			V
Mechanical Data					
M1	DC terminals, SI Units	4	–	6	Nm
M2	AC terminals, SI Units	8	–	10	Nm


## SKiiPPACK®

### SK integrated intelligent Power PACK halfbridge SKiiP

### 1202 GB 061 - 360 CTV <sup>7,9)</sup>

Preliminary Data

Case S3



### Features

- Short circuit protection, due to evaluation of current sensor signals
- Isolated power supply
- Low thermal impedance
- Optimal thermal management with integrated heatsink
- Pressure contact technology with increased power cycling capability, compact design
- Low stray inductance
- High power, small losses
- Over-temperature protection

- 1) T<sub>heatsink</sub> = 25 °C, unless otherwise specified
- 2) CAL = Controlled Axial Lifetime Technology (soft and fast) without driver
- 3) Driver input to DC link / AC output to DC link / AC output to heatsink
- 4) with Semikron-DC link (low inductance)
- 5) other heatsinks on request
- 6) C - Integrated current sensors  
T - Temperature protection  
V - 15 V or 24 V power supply
- 7) AC connection busbars must be connected by the user; copper busbars available on request  
options available for driver:  
U - DC link voltage sense  
F – Fiber optic connector
- 8) "s" referenced to temperature sensor
- 9) NPT-technology with homogeneous current-distribution