

DRAWING No.

A3

THIRD ANGLE PROJECTION

DO NOT SCALE

USED ON

TECH

VI-415-DP, VI-415-2

253-560

10.795

40

17.8

21

63.0

69.85

20

17.8

24.0

30.5

38.1

10.795

40

17.8

21

63.0

69.85

20

17.8

24.0

30.5

38.1

DRIVER: OKI MSM58292, HD61603

DIGIT HEIGHT 17.8mm (0.7")

DISPLAY MODEL NUMBER NOTATION

VIM - 808 - DP - RC - S - LV - N

APPLICATION

Blank for watch,
C: Calculator,
E: Instrument,
D: Dot Matrix,
G: Graphic

DRIVE SCHEME

Blank for Static,
M: Multiplex

MODEL NUMBER

253-560

CONNECTOR TYPES

1: Pin type (Pins not supplied)
2: Elastomeric (Zebra) Type
DP: Epoxy DIL pins Provided

DRIVE VOLTAGE*

UV: 3.3V for Multiplexing
HV: 3.3V-4.7V for Multiplexing

FLUID

S: Standard
W: Wide temperature*

POLARIZER GRADE

RC: Commercial Reflective
FC: Commercial Transmissive
C: Clear Commercial Reflective
RH: Reflective High stability
FH: Transmissive High stability
TH: Transmissive, High stability

MODE

Blank for positive
N: Negative

VIEW DIRECTION

contact surface

For elastomer or zebra

For pins or Clip-on-connector

Epoxy DIL Pins

NOTE: For DP, Standard pin length 6.35 mm (0.25"). Maximum 14.5 mm, pin pitch 2.54 mm

For other Types of pins and pin pitch, please refer to P.18

7 SEGMENT

14 SEGMENT

16 SEGMENT

(Digit number starts from right to left)

CHECKED

TRACED

DRAWN

ISSUE

DATE

AMENDMENT

ESTD WT

ACTL WT

DIMENSIONS IN

SCALE

TOLERANCES UNLESS OTHERWISE STATED

LINEAR ±

ANGULAR ±

MATERIAL & SPEC.

PROTECTIVE FINISH

TRIDENT MICROSYSTEMS LIMITED

55 Ormside Way Redhill
Surrey RH1 2LS United Kingdom
Tel: (0737) 765900 Fax: (0737) 771908

TITLE:

DRAWING No.

A3