

Safety Connection Systems

Safety Wired Distribution Box, Single-Channel N.C. plus Individual N.O. Enunciation

Specifications

Body	Red PBT
Connector Insert	PBT
Receptacle Shell	Nickel-plated brass
Contacts	Gold-plated palladium/nickel
Cable	Oil-resistant yellow PVC jacket, (12) 18AWG conductors
Cable O.D.	9.8mm (0.39in)
Enclosure Rating	IP67, NEMA 6P
Temperature	-20°C to +105°C (-13°F to +221°F)



Features

- Prewired for single-channel (N.C.) safety with enunciation
- 8 safety-wired 4-pin DC micro connectors
- Individual enunciation output for each port
- For use in category 2 or 3 systems per EN 954-1

Product Selection

Face View of Female	Number of Ports	Illuminated	Rating	Face View of Male (1)	Cable Length—m (ft)	Catalogue Number
	8	No LED	10-30V DC	Cable	5 (16.4)	898D-P48JT-A5
					10 (32.8)	898D-P48JT-A10
Shorting Plug for unused ports						898D-41KU-DM
Patchcord, straight to straight DC Micro, ⊗ = length in meters 1, 2, 3, 5, 10 standard						889D-F4ACDM-⊗

Approximate Dimensions—mm (inches)

See 8-port dimensions on page 15-5.

Wiring Diagrams

